

VEHICLE BRAKE FLUID PRESSURE CONTROL DEVICE
WITH HYDRAULIC BOOSTER

CROSS REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of Japanese Patent Applications No. 2001-24190 filed on January 31, 2001 and No. 2001-302614 filed on September 28, 2001, the contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

10 The present invention relates to a vehicle brake fluid pressure control device with a hydraulic booster to be used during normal braking control operations, in particular, applicable to an electric vehicle that does not use engine vacuum.

15 2. Related art

20 In a conventional hydro booster or an EHB (Electro Hydraulic Brake), brake pressure to be used during normal braking is amplified by using a high capacity accumulator (e.g., refer to Japanese patent No. 2,765,570).

25 However, in the hydro booster or EHB, the high pressure maintained at all times with the high capacity accumulator. Therefore, it is necessary for the brake system to be equipped with a fail-safe mechanism for ensuring the high pressure so that the brake system is complicated. Further, this brake system has a drawback that nitrogen gas or the like for maintaining the high pressure may leak through a seal, resulting in that not only the

high pressure may not be maintained but also the leaked nitrogen gas or the like may enter into a brake piping conduit.

Furthermore, an urgency brake control such as the ABS control, the TCS control or vehicle stability control, which are executed during a vehicle running, requires quick responsiveness to brake fluid pressure applied by a pump. In order to implement the quick responsiveness to pressure, a brake device having a brake fluid amount amplifier provided between a master cylinder and a wheel cylinder has been proposed (e.g., refer to Japanese patent publication No. 10-35459).

In this brake device, it is assumed that the pump is used only during the urgency control operations, but not during the normal braking operation. Accordingly, while a problem of the quick responsiveness to pressure still remains in view of a size or efficiency of the motor, it is very difficult to provide a system or control that can endure the highly frequent use at the normal braking operations.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a brake fluid control device with a hydraulic booster, which is capable of boosting up the brake pressure without using the high capacity accumulator.

It is another object of the present invention to provide a brake fluid control device with a hydraulic booster, which is capable of having quick responsiveness to a brake fluid pressure applied by a pump during an urgency control operation and further

boosting up the brake pressure in use of the pump during a normal braking operation.

According to the present invention, a brake booster supplies brake fluid to the wheel cylinder, which is larger than brake pressure generated in the master cylinder. A fluid pressure regulating unit regulates a differential pressure between the brake pressure in the master cylinder and that in the wheel cylinder. The brake booster has pump unit, which sucks and discharges the brake fluid directly supplied to the wheel cylinder, and a pressurizing flow amount amplifying unit, which amplifies an amount of the brake fluid discharged from the pump unit for supplying to the wheel cylinder. A first pipeline (A1) transmits the brake fluid discharged from the pressurizing flow amount amplifying unit to the wheel cylinders. A second pipeline (A2) transmits the brake fluid discharged from the pump unit directly to the wheel cylinders. A flow amount amplification changing unit selects one of the first and second pipelines (A1, A2) as a pressurizing path to the wheel cylinder.

Therefore, the differential pressure between the brake fluid pressure in the master cylinder and that in the wheel cylinders is secured by the brake booster in cooperation with the fluid pressure regulating unit. Thus the brake pressure boost is realized without a high capacity accumulator.

Since the flow amount amplification changing unit selects one of the first and second pipelines as the pressurizing path, the brake fluid control device according to this invention has high responsiveness to brake fluid pressure applied by the pump

during the urgency brake control and also an adequate amplifying feature for further boosting up an amount of the brake fluid supplied by the pump during the normal braking control.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will be understood more fully from the following detailed description made with reference to the accompanying drawings. In the drawings:

10
15

FIG. 1 is a schematic view of a brake system according to a first embodiment of the present invention;

FIG. 2 is a flowchart showing a process executed by a brake control ECU in the first embodiment;

FIG. 3 is a flowchart showing a process executed at step 106 of FIG. 2;

FIG. 4 is a flowchart showing a process executed at step 108 of FIG. 2;

FIG. 5 is a flowchart showing a process executed at step 111 of FIG. 2;

20

FIG. 6 is a timing diagram showing the operation of the brake system;

FIG. 7 is a schematic view of a brake system according to a second embodiment of the present invention;

25

FIG. 8 is a schematic view of the brake system of FIG. 7, showing typically constructions of control valves;

FIG. 9 is a schematic view of a brake system according to a third embodiment of the present invention;

FIG. 10 is a schematic view of a brake system of FIG. 9,
showing typically constructions of control valves;

FIG. 11 is a schematic view of a brake system according
to a fourth embodiment of the present invention;

5 FIG. 12 is a schematic view of a brake system of FIG. 11,
showing typically constructions of control valves;

FIG. 13 is a schematic view of a brake system according
to a fifth embodiment of the present invention;

10 FIG. 14 is a schematic view of a brake system of FIG. 13,
showing typically constructions of control valves;

FIG. 15 is a schematic view of a brake system according
to a sixth embodiment of the present invention;

FIG. 16 is a schematic view of a brake system according
to a seventh embodiment of the present invention;

15 FIG. 17 is a schematic view of a brake system according
to an eighth embodiment of the present invention;

FIG. 18 is a schematic view of a brake system according
to a ninth embodiment of the present invention;

20 FIG. 19 is a schematic view of a brake system according
to a tenth embodiment of the present invention;

FIG. 20 is a schematic view of a brake system according
to an eleventh embodiment of the present invention;

FIG. 21 is a schematic view of a brake system according
to a twelfth embodiment of the present invention;

25 FIG. 22 is a schematic view of a brake system according
to a thirteenth embodiment of the present invention;

FIG. 23 is a schematic view of a brake system according

to a fourteenth embodiment of the present invention;

FIG. 24 is a schematic view of a brake system according to a fifteenth embodiment of the present invention;

FIG. 25 is a schematic view of a brake system according to a sixteenth embodiment of the present invention;

FIG. 26 is a schematic view of a brake system according to a seventeenth embodiment of the present invention;

FIG. 27 is a schematic view of a brake system according to an eighteenth embodiment of the present invention;

FIG. 28 is a schematic view of a brake system according to a nineteenth embodiment of the present invention;

FIG. 29 is a schematic view of a brake system according to a twentieth embodiment of the present invention;

FIG. 30 is a schematic view of a brake system according to a twenty-first embodiment of the present invention;

FIG. 31 is a schematic view of a brake system according to a twenty-second embodiment of the present invention;

FIG. 32 is a schematic view of a brake system according to a twenty-third embodiment of the present invention;

FIG. 33 is a schematic view of a brake system according to a twenty-fourth embodiment of the present invention;

FIG. 34 is a schematic view of a brake system according to a twenty-fifth embodiment of the present invention;

FIG. 35 is a schematic view of a brake system according to a twenty-sixth embodiment of the present invention;

FIG. 36 is a flowchart showing a process executed by the brake control ECU when the brake control ECU executes ABS control;

FIG. 37 is another flowchart continuing from that of FIG.

36;

FIG. 38 is a flowchart showing ABS control processing; and

FIG. 39 is a timing diagram showing an operation of the

brake system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(First embodiment)

A brake system incorporated in a vehicle according to a first embodiment of the present invention is described. As referring to FIG. 1, the brake system has a brake control ECU 1 that executes each vehicle control.

The brake system is controlled according to a pressing operation of the brake pedal 2. The brake pedal 2 is connected to a master cylinder (M/C) through a push rod or the like. When the brake pedal is pressed by a driver, a piston of the M/C is pushed by the push rod, and therefore brake fluid pressure corresponding to the pedal pressure is generated in the M/C 3. The M/C 3 has a master reservoir 3a that provides brake fluid to the M/C 3 and reserves surplus brake fluid of the M/C 3.

The M/C pressure generated in the M/C 3 is transferred to the respective wheel cylinders (W/C) 4, 5 attached to respective wheels 4a, 5a through first brake piping. In FIG. 1, the first brake piping for transferring the M/C cylinder pressure in the primary chamber of the M/C 3 is described, but a second brake piping having the same construction as the first brake piping and for transferring M/C pressure of the secondary chamber in

the M/C 3 is also employed in the brake system. However, for simplicity, the secondary brake piping is not shown in FIG. 1. In the following explanation, the first brake piping is explained as one example, but the second brake piping is the same.

5 The first brake piping includes a pipeline (main pipeline) A that connects the M/C 3 to the W/C 4, 5. This pipeline A is equipped with a pressure regulating reservoir 6 and a pump 8 that is driven by a motor 7. The pump 8 sucks brake fluid from the M/C 3 side through the pressure regulating reservoir 6 and discharges it to the W/C 4, 5 side. The motor 7 and the pump 8 constitutes a pump unit.

10 The pressure regulating reservoir 6 has first and second reservoir ports 6a, 6b, a reservoir piston 6c, a valve element 6d that moves in conjunction with the reservoir piston 6c, a valve seat 6e on which the valve element 6d rests. The first reservoir port 6a is connected to the M/C 3 side, and the second reservoir port 6b is connected to the pump 8 side. When the pressure regulating reservoir 6 reserves a predetermined amount of brake fluid, the valve element 6d rests on the valve seat 6e. Thus,
15 the brake fluid pressure applied to the pump 8 is restricted so as not to provide the high pressure brake fluid to the pump 8 through the second reservoir port 6b. The pump 8 may be a rotary pump such as a trochoid pump. The pump 8 sucks and discharges brake fluid according to rotation of the gears equipped in the
20 pump 8.

25 The pipeline A branches out into two pipelines (a first pipeline and a second pipeline) A1, A2 downstream from a discharge

port of the pump 8. An amplifying piston 9 and a first control valve 10 is employed in the pipeline A1, and a second control valve 11 is employed in the pipeline A2. The first and second pipelines A1, A2, respectively, form pressurizing paths for
5 pressurizing brake fluid to be supplied to the W/C 4, 5 with the pump 8. The pressurizing paths can be switched by the first and second control valves 10, 11. The amplifying piston constitutes a brake fluid amplification unit.

The amplifying piston 9 has a step piston 9a. This step piston 9a is so constructed that its pressure-receiving surface on a side of the W/C 4, 5 is wider than that on a side of the pump 8. The smaller pressure-receiving surface defines a part of a first chamber 9b, and the wider pressure-receiving surface defines a part of a second chamber 9c. The second chamber 9c is connected to the pipeline A upstream from the pressure regulating reservoir 6 via a pipeline B. A check valve 12 is employed to the pipeline B to permit the brake fluid to flow only from the M/C 3 side to the second chamber 9c. Thus, when the brake fluid discharged from the pump 8 is provided to a first chamber 9b,
10 an amount of the brake fluid greater than that provided to the first chamber 9b is delivered to the W/C 4, 5 from the second chamber 9c. Further, this amplifying piston 9 has a spring 9d for urging the step piston 9a toward an upstream side (the pump 8 side). Therefore, if differential pressure between the first
15 chamber 9b and the second chamber 9c is lower than a predetermined value, the first chamber 9b is reduced by the step piston 9a.

Seal members 9e, 9f such as O-rings are provided around

a large diameter portion and small diameter portion of the step piston 9a, respectively, to maintain the differential pressure between the first and second chambers 9b, 9c. A third chamber 9g is defined by a stepped portion of the step piston 9a and a wall that is used as guide wall (guide wall) on which the step piston 9a slide. The third chamber 9g is also connected to the pipeline A upstream from the pressure regulating reservoir 6 via a pipeline C so that negative pressure is not generated in the third chamber 9g when the step piston 9a slides on the guide wall.

Each of the first and second control valves 10, 11 is a two position valve that can switch between an open position and a differential pressure position (or close position). The first control valve 10 adjusts so that the fluid pressure of the second chamber 9c side is lower than that on the W/C 4, 5 side when the first control valve 10 is set to the differential pressure position. The second control valve 10 adjusts so that the fluid pressure of the W/C 4, 5 side is lower than that on the side of the discharge port of the pump 8 (the first chamber 9b side). The valve positions of the first and second control valves 10, 11 are set to the positions shown in FIG. 1 while their solenoids are not energized.

Further, the pipelines A1, A2 are joined into one pipeline downstream from the first and second control valves 10, 11, and then the pipeline A branches out into two pipelines A3, A4 again. The pipeline A3 is connected to the W/C 4, and the pipeline A4 is connected to the W/C 5. A pressurization control valve 13 is employed in the pipeline A3, and a pressurization control valve 14 is employed in the pipeline A4. Each of the pressurization

control valves 13, 14 is a two position valve that can switch between an open position and a close position. Thus, each of the pipelines A3, A4 is selectively opened and closed by the pressurization control valves 13, 14. Valve positions of the
5 pressurization control valves 13, 14 are set to the position shown in FIG. 1 while their solenoids are not energized.

The pipeline A3 between the pressurization control valve 13 and the W/C 4 is connected to the pipeline between the pressure regulating reservoir 6 and the pump 8 via a pipeline D1. The
10 pipeline A4 between the pressurization control valve 14 and the W/C 5 is connected to the pipeline between the pressure regulating reservoir 6 and the pump 8 via a pipeline D2. A depressurization control valve 15 is disposed in the pipeline D1, and a
15 depressurization control valve 16 is disposed in the pipeline D2. Each of the depressurization control valves 15, 16 is a two position valve that can switch between an open position and a close position. Thus, each of the pipelines D1, D2 is selectively
opened and closed by the depressurization control valves 15, 16. Valve positions of the depressurization control valves 15, 16
20 are set to the positions shown in FIG. 1 while their solenoids are not energized.

Further, the pipeline A between the M/C 3 and the pressure regulating reservoir 6 communicates with a pipeline between the pump 8 and the amplifying piston 9 or the second control valve
25 11 via a pipeline E. A linear valve 17 is employed in the pipeline E, thereby controlling brake fluid differential pressure between the discharge port side pressure of the pump 8 and the M/C pressure.

For example, the above-mentioned differential pressure is duty controlled by an electric current applied to the linear valve 17.

In the first brake piping, various kinds of sensors that detect conditions of elements are provided. Namely, a pedal pressure sensor (pedal detecting unit) 18 is provided in the brake pedal 2. A M/C pressure sensor 19 is provided in the pipeline A between the M/C 3 and the pressure regulating reservoir 6. A W/C pressure sensor 20 is provided in the pipeline A between one of the first and second control valves 10, 11 and one of the pressurization control valves 13, 14. A rotation number sensor 21 that senses rotation number of the motor 7 is disposed near the motor 7. Wheel speed sensors 22, 23 that sense respective wheel speeds of wheels 4a, 5a are disposed near rotors of wheels 4a, 5a. A stroke sensor 24 that senses sliding amount of the step piston 9a is employed in the amplifying piston 9. Each of these sensors 18-24 generates each sensing signal, which is input to the brake control ECU 1.

Various kinds of sensing signals from vehicle condition sensor 25 such as a yaw-rate sensor, a voltage from a battery 26 (referred to herein battery voltage), and an ON/OFF signal of an ignition switch 27 are input to the brake control ECU. The brake control ECU 1 is capable of exchanging information with a vehicle control ECU 28 such as a power train control ECU (e.g., an engine ECU).

The brake control ECU 1 controls each of the control valves 10, 11, 13-17 and a rotation driving force of the motor 7 according

to the input signals or the like, and detects malfunction based on whether braking operation is normal or not, whether each of the elements of the first brake piping acts normal or the like. Further, it activates indication lamp 29 provided in the vehicle or the like based on the detecting results. For example, the brake control ECU 1 detects a stroke end of the step piston 9a based on the sensing signal from the stroke sensor 24, so that the pressurizing path is adequately selected. The brake control ECU 1 compares W/C pressure with duty ratio of the electric current of the linear valve 17, to judge whether the w/c pressure is adequately pressurized.

According to the brake system of this embodiment, one of the pipelines A1, A2 is appropriately selected as the pressurizing path to the W/C 4, 5 by switching positions of the first and second control valves 10, 11. Further, the duty ratio of the electric current to the linear valve 17 is set from time to time according to the vehicle conditions so the W/C 4,5 are appropriately pressurized.

In this embodiment, the pipeline A1 is selected as the pressurizing path when the W/C 4, 5 are low pressure, for example, at the beginning of braking operation (W/C low pressure timing), while the pipeline A2 is selected as the pressurizing path when the W/C 4, 5 become high pressure (W/C high pressure timing).

At First, when the brake pedal 2 is stepped on quickly, during the W/C low pressure timing, a great amount of brake fluid for pressurizing is needed because consumption of the brake fluid in the W/C 4, 5 is large. Therefore, in this case, the brake control

ECU 1 sets the first control valve 10 to the open position and sets the second control valve 10 to the differential pressure position. Thus, the pipeline A1 is selected as the pressurizing path. Next, the brake control ECU 1 is operative to keep differential pressure between the discharge pressure of the pump 8 and the fluid pressure of the M/C 3 to a rated value by establishing the duty ratio of the electric current to the linear valve 17. In this timing, a ratio of the discharging pressure of the pump 8 to the required fluid pressure to be applied to the W/C 4, 5 is set to a value equal to the pressure-receiving surface area ratio of the step piston 9a. Therefore, the brake fluid discharged from the pump 8 flows into the first chamber 9b in a state that the linear valve 17 keeps the differential pressure between the M/C pressure and the discharge pressure of the pump 8. As a result, the step piston 9a is pushed toward a downstream side against a biasing force of the spring 9d so that the brake fluid in the second chamber 9c is pushed out to the W/C 4, 5 side to pressurize the W/C 4, 5.

Accordingly, when the pipeline A1 is selected, the brake pressure is boosted up under a help of the linear valve 17. Further, the W/C 4, 5 side are pressurized by the brake fluid whose volume is larger than that of the discharging brake fluid from the pump 8 based on the pressure-receiving surface difference of the step piston 9a. Thus, though a load of the pump 8 increases, but a great amount of highly pressurized brake fluid can be secured.

Since the best efficiency (motor efficiency) region of the motor 7 for driving the pump 8 is limited, it is the most preferable

that the motor 7 is used within the limited region, but if high pressure response in a wider pressure range is required, the motor 7 has to be used out of the region. In this case, it is not preferable because not only the load of the motor 7 increases, but also consumption of the current by the motor 7 increases. On the other hand, according to this embodiment, the pressurizing paths are constituted by two paths, that is, one path is the pipeline A1 using pressure-receiving surface difference for pressurizing the W/C 4, 5 with the brake fluid amount greater than that discharged from the pump 8, the other path is the pipeline A2 through which the W/C 4, 5 is pressurized directly by the pump 8. Then, the two paths are changed over according to the demand. Therefore, it is possible to secure high pressure response without using the motor 7 outside the best efficiency region. In this manner, the motor 7 is used within the best efficiency region and the high pressure response is secured by using the pipelines A1, A2. This advantage is also achieved even when a flow of the brake fluid is slow at a low temperature.

The M/C pressure is introduced to the third chamber 9g via the pipeline C, when the step piston 9a slides on the guide wall. Thus, the volume of the brake fluid provided from the M/C 3 correspond to the consumption volume of the brake fluid in the W/C 4, 5.

At the W/C high pressure timing, the W/C pressure becomes high to extent that it is not necessary to pressurize the W/C 4, 5 with the brake fluid amount greater than that discharged from the pump 8. At this time, the W/C is sufficiently pressurized

by driving the motor 7 in the best efficiency region. So, the first control valve 10 is set to the differential pressure position, the second control valve 11 is set to the open position, and the pipeline A2 is selected as the pressurizing path. Then, a differential pressure is generated between the discharge pressure by the pump 8 and the brake fluid pressure of the M/C 3 side by determining the duty ratio of the electric current of the linear valve 17. In this manner, the brake pressure is boosted up by the linear valve 17, and the W/C 4, 5 side are pressurized directly by the brake fluid discharged from the pump 8. Thus, as the pipeline A1 is selected, it is unnecessary to push the step piston 9a. Therefore, the load of the pump 8 is reduced, and it is possible to use the motor 7 in the best efficiency region.

Next, the processing executed by the brake control ECU 1 of the vehicle brake system of this embodiment is described. FIG. 2 shows main routine executed by the brake control ECU 1.

First, at step 101, the motor 7 and the linear valve 17 are set OFF as initializing processing. So, the pump 8 stops discharging the brake fluid, and the linear valve 17 does not generate the differential pressure. Namely, the brake pressure of the M/C 3 and that of the W/C 8 become the same pressure one another. At step 102, whether the ignition switch 27 is ON or not is determined. The processing advances to step 103 in response to an affirmative determination (Yes), while advancing to an end of this routine in response to a negative determination (No).

At step 103, the pedal conditions of the brake pedal 2 such as pedal pressure and the M/C pressure are calculated based on

the sensing signal from the pedal pressure sensor 18 and the M/c pressure sensor 19. Next, the processing advances to step 104, and whether the brake pedal 2 is operated or not is determined. For example, this step determines whether the pedal pressure calculated based on the sensing signal from the pedal pressure sensor 18 is zero or not. The processing advances to step 105 in response to an affirmative determination (Yes), while returning to step 101 in response to a negative determination (No).

At step 105, the motor 7 is set ON with 100% duty, and the brake fluid is sucked and discharged by the pump 8. Next, the processing advances to step 106, and the duty ratio of the electric current of the linear valve 17 or the like is calculated for a control processing of the linear valve 17, that is, for estimating the differential pressure generated by the linear valve 17.

FIG. 3 shows the control processing of the linear valve 17 executed by the brake control ECU 1. First, at step 201, whether a sudden brake operation is performed or not. That is, whether a brake force assisting is necessary or not is determined. For example, this step is determination is carried out based on a change ratio of the pedal pressure of the brake pedal 2 or a change ratio of the M/C pressure that is calculated at step 103. The processing advances to step 202 in response to a negative determination (No) as the normal brake mode at which an assist to brake force is unnecessary. Then, the W/C pressure corresponding to pedal pressure applied to the brake pedal 2 is calculated based on a relationship between the pedal pressure and target W/C pressure at the normal brake mode. For example,

as shown in FIG. 3, the target W/C pressure is set so that the W/C pressure will be seven times (i.e., amplifying ratio 7) as large as the pedal pressure (or the M/C pressure). While, the processing advances to step 203 in response to an affirmative determination (Yes) as the assist brake mode at which the assist to the brake force is necessary. Then, the W/C pressure corresponding to pedal pressure applied to the brake pedal 2 is calculated based on a relationship between pedal pressure and target W/C pressure at the assist brake mode. For example, as shown in FIG. 3, the target W/C pressure is set so that the W/C pressure will be seven times plus 3MPa as the pedal pressure (or the M/C pressure).

Next, the processing advances to step 204, whether the amplifying piston bypass change is executed or not is determined. Namely, whether the pipeline A1 or A2 is selected as the pressurizing path is determined. This processing is determined by a flag or the like that is set when the amplifying piston bypass change is executed at amplifying piston bypass change processing (See step 108) mentioned later.

The processing advances to step 205 in response to a negative determination (No), and a control target pressure (differential pressure) ΔP necessary for the linear valve 17 is calculated when the amplifying piston bypass change is not executed, that is, when the pipeline A1 is selected as the pressurizing path. In this case, the control target pressure ΔP is calculated based on a predetermined relationship between the M/C pressure and the discharge pressure by the pump 8 shown in FIG. 3. Because both

sides of brake pressure of the linear valve 17 correspond to the M/C pressure and the discharging pressure of the pump 8.

On the other hand, the processing advances to step 206 in response to an affirmative determination, and a control target pressure (differential pressure) ΔP necessary for the linear valve 17 is calculated when the amplifying piston bypass change has been executed, that is, the pipeline A2 is selected as the pressurizing path. In this case, the control target pressure ΔP is calculated based on a predetermined relationship between the M/C pressure and the W/C pressure shown in FIG. 3. Because both sides of brake pressure of the linear valve 17 correspond to the M/C pressure and the W/C pressure.

Then, the processing advances to step 207, and a current amount (target current) to the linear valve 17, which is necessary to realize the control target pressure ΔP calculated at steps 205, 206, is calculated. For example, a relationship between the current amount to the linear valve 17 and the differential pressure generated by the linear valve 17 is shown in FIG. 3. Therefore, the target amount that corresponds to the control target pressure ΔP is calculated based on its relationship.

Next, at step 208, a battery voltage input calculation for calculating battery voltage is executed. Then, the processing advances to step 209, the duty ratio of current to the linear valve 17 is calculated based on the target current calculated at step 207 and a relationship between the target current and battery voltage. Namely, the higher the battery voltage is, the shorter the required time for providing a current to the linear

valve 17. Thus, the duty ratio is adjusted depending on the battery voltage. Then, the processing advances to step 210, and the current corresponding to the duty ratio calculated at step 209 is applied to the linear valve 17.

5 At step 211, a feedback current from the linear valve 17 is calculated. For example, the feedback current is calculated by inputting a voltage between both sides of the resistance, which is connected in series to the coil of the linear valve 17 for detecting current amount, to the CPU of the brake control ECU 1.

10 Next, the processing advances to step 212, the calculated feedback current and the target current calculated at step 207 are compared with each other, and whether both of them are coincident with each other or not is determined. Then, the processing advances to an end if the feedback current is the target current, the processing advances to step 213 if the feedback current is not the target current. At step 213, a duty ratio revision calculation is executed. In this processing, a deviation ΔA between the feedback current and the target current is calculated, 15 a current amount ($\Delta A x k$) applied to the linear valve 17 that is necessary to compensate the deviation ΔA is calculated, and a duty ratio revision amount of the current to the linear valve 17 is calculated. Next, a duty ratio amendment output is executed. Namely, the calculated current based on the calculated duty ratio 20 is applied to the linear valve 17. Then, the processing advances to an end after the real W/C pressure and target brake pressure become coincident with each other.

After the linear valve control processing is over, the processing advances to step 107 to calculate the W/C pressure based on the sensing signal from the W/C sensor 20. Then the processing advances to step 108 to execute a amplifying piston
5 bypass change processing, that is, a valve position change processing of the first and second control valves 10, 11. This amplifying piston bypass change processing is shown in FIG. 4.

As shown in FIG. 4, at step 301, changing trigger sensing signal input calculation is executed based on the each input signal
10 from the each of sensors 18-21, 24. In this processing, various kinds of calculation for determining a change timing of the pressurizing path, i.e., the pipeline A1 or A2, are executed. For example, the W/C pressure, the M/C pressure, the differential pressure between the W/C pressure and the M/C pressure, the differential pressure between the discharge pressure by the pump
15 8 and the W/C pressure, the pedal pressure of the brake pedal 2, the rotation number of the motor 7, an input current to the motor 7, a stroke of the step piston 9a, an input current to the linear valve 17, the duty ratio of the current to the linear valve
20 17, and the like, are calculated.

The discharge pressure by the pump 8 is calculated based on the duty ratio of the current to the linear valve 17 because the discharge pressure has correlation with the duty ratio of current. The input current to the motor 7 is calculated based
25 on a motor target current that is calculated at a motor rotation number control processing (See step 405 shown in FIG.5). The other calculations are calculated based on the sensing signals from

various sensors 18-21, 24.

Next, at step 302, whether the amplifying piston 9 is changed or not, that is, whether or not the pipeline A2 is selected as the pressurizing path is determined. The processing advances to step 303 in response to a negative determination (No). For example, the negative determination is evolved when the pipeline A1 is selected as the pressurizing path because the amplifying piston bypass change processing (See step 304) has not been executed yet.

At step 303, whether an amplifying piston bypass changing condition is satisfied or not is determined. Specifically, the W/C pressure > predetermined pressure X1, the discharge pressure of the pump 8 > predetermined pressure X2, the differential pressure between the W/C pressure and the M/C pressure > predetermined pressure X3, the differential pressure between the discharge pressure of the pump 8 and the W/C pressure > predetermined pressure X4, the M/C pressure > predetermined pressure X5, the pedal pressure of the brake pedal 2 > predetermined pressure X6, the rotation number of the motor 7 > predetermined number X7, an input current to the motor 7 > predetermined amount X8, stroke of the step piston 9a > predetermined length X9, an input current to the linear valve 17 > predetermined amount X10, the duty ratio of the current to the linear valve 17 > predetermined value X11, and the like are corresponding to the conditions. When at least one of the conditions is satisfied, the affirmative determination is evolved.

The processing advances to step 304 in response to an affirmative determination (Yes). Then, the first control valve

10 is set to the differential pressure position, and the second control valve 11 is set to the open position. Moreover, after setting the flag indicating that the amplifying piston bypass change processing is executed, the processing advances to an end.

5 If this processing is achieved, the affirmative determination is evolved at step 204 when the linear valve control processing is executed thereafter.

On the other hand, the processing advances to step 305 in response to a negative determination (No), and whether a pressurizing requirement at the normal braking is large or not is determined. Namely, at the normal braking, if the requirement is not large, high responsiveness to a brake fluid pressure is not desired. Accordingly, in this case, the brake control ECU 1 selects the pipeline A2 as the pressurizing path. Specifically, the differential pressure between the target W/C pressure and real W/C pressure > predetermined pressure X12, an increase ingredient of the pedal pressure of the brake pedal 2 > predetermined value X13, an increase ingredient of the W/C pressure > predetermined value X14, and an increase ingredient of the M/C pressure > predetermined value X15 are the conditions of this processing. When at least one of the conditions is satisfied, an affirmative determination (Yes) is evolved. The target W/C pressure is a target value of the W/C pressure to be required based on the pedal pressure of the brake pedal 2 and is calculated by the brake control ECU 1.

In this processing, if the affirmative determination is evolved, the pipeline A1 is maintained as the pressurizing path

and this processing ends. On the other hand, the processing advances to step 306 in response to a negative determination (No), and whether high pressurize response control is required or not is determined. This determination is executed based on the requirement for starting a TCS control, a vehicle stability control or an assist control to the brake force, that is, an urgency brake control to be executed based on a vehicle behavior. For example, the requirement is judged based on the calculation results of the sensing signals from the vehicle condition sensor 25 or the wheel speed sensors 22, 23. Whether the high pressurize response control is required or not can be determined based on the flag that is set when the urgency control is executed.

The processing advances to step 304 in response to a negative determination (No) at step 306, and the pipeline A2 is selected as the pressurizing path as mentioned-above and, then, the processing advances to an end. On the contrary, the processing advances to end in response to an affirmative determination (Yes). In this case, the pipeline A1 is maintained as the pressurizing path.

The processing advances to step 307 in response to a negative determination (No) at step 302. Then, whether the amplifying piston bypass change conclusion condition is satisfied or not is determined. Specifically, the W/C pressure < predetermined pressure X1, the discharge pressure by the pump 8 < predetermined pressure X2, the differential pressure between the W/C pressure and the M/C pressure < predetermined pressure X3, the differential pressure between the discharge pressure of the pump 8 and the

W/C pressure < predetermined pressure X4, the M/C pressure < predetermined pressure X5, the pedal pressure of the brake pedal 2 < predetermined pressure X6, the rotation number of the motor 7 < predetermined number X7, the input current to the motor 7 < predetermined amount X8, the stroke of the step piston 9a < predetermined length X9, the input current to the linear valve 17 < predetermined amount X10, the duty ratio of the current to the linear valve 17 < predetermined value X11, and the like are the conditions. When at least one of the conditions is satisfied, the affirmative determination is evolved. Incidentally, these conditions are opposite to the conditions at step 303.

The processing advances to an end in response to a negative determination (No). In this case, the pipeline A2 is maintained as the pressurizing path. On the other hand, the processing advances to step 308 in response to an affirmative determination (Yes) to execute the amplifying piston bypass change conclusion processing. Namely, the first control valve 10 is set to the open position, and the second control valve 11 is set to the differential pressure position, thereby selecting the pipeline A1 as the pressurizing path again. Then, the processing advances to an end. If this processing is achieved, the negative determination is evolved at step 204 when above-mentioned linear valve control processing is executed thereafter.

After the amplifying piston bypass change processing, steps 109, 110 determine whether a condition for limiting a rotation number of the motor 7 at a motor rotation restriction processing (See step 111) is satisfied or not.

At step 109, whether brake fluid pressurization according to a depressing state of the brake pedal 2 is required or not is determined. This determination is made by comparing the pedal pressure or the M/C pressure calculated at step 103 with the previous calculation result. The processing advances to step 110 in response to a negative determination (No), while returning to step 102 in response to an affirmative determination (Yes). At step 110, whether the W/C pressure is increasing or not is determined. This process determination is made by comparing the W/C pressure calculated at step 107 with the previous calculation result. Then, the processing advances to step 111 in response to a negative determination (No), while returning to step 102 in response to an affirmative determination (Yes).

That is, it is necessary to further increase the W/C pressure when the brake fluid pressurization according to the depressing state of the brake pedal 2 is required or when the W/C pressure is increasing. Therefore, the processings mentioned- above is used to determine whether the condition for limiting the rotation number of the motor 7 is satisfied or not. If the condition is not satisfied, the motor 7 is rotated continuously.

Next, the processing advances to step 111 to execute the motor rotation number control processing. FIG. 5 shows a flow chart of this processing.

First, at step 401, whether the vehicle is stop or not is determined. If an affirmative determination is evolved, the increase of the W/C pressure by the pump 8 for stopping the vehicle is unnecessary. Therefore, the processing advances to step 402

to stop the motor 7, and, then, the processing advances to an end. While, if negative determination is evolved, the processing advances to step 403 to estimate temperature of the brake fluid. For example, this temperature is estimated based on coolant
5 temperature of the engine, which is detected by the vehicle condition sensor 25.

At step 404, the target rotation number of the motor 7, which is required in order to discharge desired amount brake fluid from the pump 8 immediately when high pressurize response is required, is calculated based on a characteristic relationship between the brake fluid temperature and required rotation number as shown in FIG. 4. That is, viscosity of the brake fluid varies depending on its temperature, and a rising rate of rotation number of the motor 7 varies depending on the temperature of the brake fluid. As shown in FIG. 5, for example, the higher the temperature of the brake fluid is, the greater the required rotation number is. Accordingly, the required rotation number of the motor 7 depends on the estimated brake fluid temperature.

The processing advances to step 405, at which a target current
20 to the motor 7 (motor target current) is calculated. Specifically, a relationship between the discharge pressure by the pump 8 and the motor target current at the target rotation number is calculated after the target rotation number is calculated at step 404. For example, the higher the discharge pressure by the pump 8 is, the
25 higher the motor target current is required. Accordingly, the target motor current is calculated depending on the discharge pressure by the pump 8.

At step 406, a duty ratio of the current to the motor 7 is calculated based on the battery voltage calculated at step 208 in consideration of a relationship between the motor target current calculated at step 405 and the battery voltage. Namely, the higher the battery voltage is, the shorter a current applying time necessary for applying the motor target current to the motor 7 is. Therefore, the duty ratio calculation depends on the battery voltage. Then the processing advances to step 407, where the current corresponding to the duty ratio calculated at step 406 is applied to the motor 7.

At step 408, a real rotation number of the motor 7 is calculated based on the sensing signal from the rotation number sensor 21. Then, the processing advances to step 409 to determine whether or not the calculated real rotation number and the calculated target rotation number are coincident with each other. The processing advances to an end in response to an affirmative determination (Yes), while advancing to step 410 in response to a negative determination (No) to execute a duty ratio revision calculation. In this processing, a deviation between the calculated real rotation number and the calculated target rotation number is calculated, and, then, a required current to the motor 7 for revising the deviation is calculated. Further, the duty revision amount of current to the motor 7 is calculated based on the required current. After the duty ratio of the current to the motor 7 is calculated, a motor duty ratio revision output processing is executed. That is, a current depending on the calculated duty ratio is applied to the motor 7. If the real

rotation number of the motor 7 is coincident with the target rotation number with this manner, the processing advances to an end.

Next, the processing advances to step 112 to determine whether or not the W/C pressure and the target W/C pressure are coincident with each other. The processing returns to step 102 in response to a negative determination (No), while advancing to step 113 in response to affirmative determination (Yes). At step 113, linear valve revision output is calculated. In this processing, a deviation ΔP between the real W/C pressure and the target W/C pressure is calculated, and the a required differential pressure amount by the linear valve 17 to revise the deviation ΔP is calculated. Further, the duty revision amount of current to the linear valve 17 is calculated based on the required differential pressure amount. After the duty ratio of the current to the linear valve 17 is calculated, the processing advances to step 114 to execute linear valve duty ratio revision output processing. That is, a current depending on the calculated duty ratio is provided to the linear valve 17. If the real W/C pressure is coincident with the target W/C pressure with this manner, the processing returns to step 112 to execute the various processing mentioned above repeatedly.

FIG. 6 is a timing diagram showing the operation of the brake system on executing the processings as shown in FIGs. 2-5. The vehicle speed calculated based on the sensing signal from the wheel speed sensors 22, 23, the pedal pressure of the brake pedal 2, the brake fluid pressure (the discharge pressure by the pump 8, the M/C pressure, and the W/C pressure), switchings of

the first and second control valves 10, 11, the duty ratio of the current to the linear valve 17, and the duty ratio of the current to the motor 7 are shown in FIG. 6.

First, at W/C low pressure timing as shown in term t1-t2 when the pressure of the brake pedal 2 is just starting, the first control valve 10 is set OFF (open condition), and the second control valve 11 is set ON (differential pressure condition). Therefore, the pipeline A1 is selected as the pressurizing path. Further, the duty ratio of the current to the linear valve 17 is estimated based on the position of the first and second control valve 10, 11, and the differential pressure between the M/C 3 side and the discharge port of the pump 8 is generated by the linear valve 17. Accordingly, the amount of the brake fluid discharged by the pump 8 is amplified by the amplifying piston 9, and the amplified brake fluid whose volume is larger than that discharged by the pump 8 is supplied to the W/C 4, 5. Specifically, the fluid pressure corresponding to the brake fluid amount amplified by the pressure-receiving surface difference of the step piston 9a is generated at the W/C 4, 5. Thus, the W/C 4, 5 can be pressurized with high pressure response to the discharge pressure of the pump 8.

If the pedal pressure of the brake pedal 2 is maintained, as in term t2-t3, during a period when the pipeline A1 is selected as the pressurizing path, the brake fluid pressure of each element of the brake piping is maintained in a state as shown in term t2. In this time, the relationship between the M/C pressure and the W/C pressure is maintained without stopping the motor 7 in

this embodiment (standing condition), though the relationship can be maintained even if the motor 7 is stopped. Therefore, the discharge pressure by the pump 8 is maintained so that the high pressure response can be realized when the pedal pressure of the brake pedal 2 increases again thereafter.

Next, as in term t3-t4, if the pedal pressure of the brake pedal 2 increases again, and the brake fluid is provided to the W/C 4, 5 more fully than that discharged by the pump 8 in the same manner as term t1-t2. Then, at the W/C high pressure timing when the amplifying piston bypass change condition (See step 303) is satisfied, the amplifying piston change processing is executed. That is, the first control valve 10 is set ON (differential pressure condition), and the second control valve 11 is set OFF (open condition). Therefore, the pipeline A2 is selected as the pressurizing path. Further, the duty ratio of the current to the linear valve 17 is estimated based on the positions of the first and second control valve 10, 11, and the differential pressure between the M/C 3 side and the discharge port side of the pump 8 is generated by the linear valve 17. Accordingly, the discharge pressure of the pump 8 becomes the W/C pressure because the discharge port side of the pump 8 communicates with the W/C 4, 5.

If the pedal pressure of the brake pedal 2 is maintained as in term t4-t5 during a period when the pipeline A2 is selected as the pressurizing path, the brake fluid pressure of each element of the brake piping is maintained similarly as in term t4. In this time, the brake control ECU 1 does not let the motor 7 stop as in the term t2-t3. Therefore, the high pressure response also

can be realized if the pedal pressure of the brake pedal 2 increases again thereafter.

Next, if the pedal pressure of the brake pedal 2 reduces as in term t5-t6, the duty ratio of the current to the linear valve 17 is estimated based on the reduced pedal pressure. As a result, the brake fluid pressure of each element of the brake piping is reduced. In this time, at the W/C pressure timing when an amplifying piston bypass change end condition (See step 307) is not satisfied, the first control valve 10 is set OFF (open condition), and the second control valve 11 is set ON (differential pressure condition). Then the pipeline A1 is selected as the pressurizing path. Therefore, the discharging brake fluid amount from the pump 8 is amplified by the amplifying piston 9, and the W/C pressure can increase with high pressure response to discharge pressure of the pump 8 as in term t1-t2.

Then, if the pedal pressure of the brake pedal 2 is maintained or reduced, the duty ratio of the current to the linear valve 17 is estimated based on the maintained or reduced pedal pressure. As a result, the brake fluid pressure of each element is reduced. Then, if the vehicle stops and the depression to the brake pedal 2 stops, the brake fluid pressure of each element of the brake piping becomes zero. During a period when pedal pressure of the brake pedal 2 is reduced, the brake control ECU 1 does not let the motor 7 stop (standing condition). However the brake control ECU 1 let the motor 7 stop when the vehicle speed is zero (See step 402). Therefore, current consumption (electric power consumption) is saved after the vehicle stops.

As described above, in the brake system of this embodiment, the differential pressure between the M/C pressure and the W/C pressure is generated by adjusting the duty ratio of the current to the linear valve 17. Therefore, the brake system having a hydraulic booster as mentioned above can realize without maintaining the high pressure constantly by the high capacity accumulator.

Additionally, the pipeline A1 provided to a amplifying piston 9 is selected as the pressurizing path at the W/C low pressure timing. The pipeline A2, which can directly transmit discharge pressure of the pump 8 to the W/C 4, 5, is selected as the pressurizing path at the W/C high pressure timing. Accordingly, the brake system in this embodiment has high pressure response only with the pump 8 at an urgency brake control timing, and, further, has a feature for boosting up the amount of brake fluid discharged from the pump 8 at normal braking control timing.

The brake system in this embodiment can realize boost up feature is use of the pump 8, the linear valve 17, the pipeline A1 with the amplifying piston 9, and the pipeline A2 without the amplifying piston 9. Therefore, even in the electric vehicle that cannot use engine vacuum, the boost up feature is realized in use of a simple and reliable brake system based on the conventional hydraulic brake piping. Moreover, the motor 7 can be used within the preferable efficiency region by switching the pressurizing path between W/C low pressure timing and W/C high pressure timing. Therefore, the brake system can endure not only the use in the urgency brake control but also a highly frequent use in the normal

brake control.

The brake fluid discharged by the pump 8 flows to spaces such as the first chamber 9b, and clearances near the seal member 9f, or the like. However, these spaces and clearances act as dampers. Accordingly, a pulsation generated by discharging brake fluid from the pump 8 can be absorbed by the spaces and clearances without employing an extra damper in the brake system.

Further, in the present brake system, the M/C 3 and the second chamber 9c are communicated via the pipeline B with the check valve 12. Therefore, if the rising rate of the W/C pressure, which is generated based on the discharge pressure of the pump 8, is slow, the W/C 4, 5 can be pressurized directly by the brake pressure generated at the M/C 3 via the pipeline B and the second chamber 9c.

Then, the minimum control range (i.e., pressure range corresponding to one unit to control) to use the linear valve 17 is estimated based on the amplifying ratio of the amplifying piston 9. Accordingly, sensitive control of the amplifying piston is available, so that control characteristics of the W/C pressure, in particular at W/C low pressure timing, can be improved.

The pipeline A2 is selected when the high pressure response is not desired during normal braking control in the pressure increase requirement is not so high, or during urgency braking control in which the high pressure response is not required (See steps 305, 306). However, the pipeline A1 may be selected instead of the pipeline A2 so as to obtain the high pressure response.

(Second embodiment)

FIG. 7 is showing a brake system according to second this embodiment. The first and second control valves 10, 11 are driven electrically in the first embodiment, but are driven mechanically in the second embodiment. The other elements of the second embodiment are similar to the first embodiment.

As shown in FIG. 7, the first and second control valves 10, 11 are driven by the brake fluid pressure in the pipeline A on the W/C 4, 5 side of the first and second control valves 10, 11 via the pipeline F1, F2. That is, the first and second valves 10, 11 are driven based on the W/C pressure. Specifically, the first and second control valves 10, 11 provided for the brake system as shown in FIG. 7 have valve constructions as shown in FIG. 8.

As shown in FIG. 8, the first control valve 10 has first and second ports 31, 32, a piston 33, a spring 34, a valve element 35 and a valve seat 36. The valve element 35 moves in conjunction with the piston 33 and rests on the valve seat 35. The first port 31 is connected to the second chamber 9c side, and the second port 32 is connected to the W/C 4, 5 side. Further, the first control valve 10 has a check valve 37 that is arranged downstream (on the W/C 4, 5 side) from the first port 31 and allows the brake fluid to flow only from the second chamber 9c side to the W/C 4, 5 side. Accordingly, at the W/C low pressure timing, the first valve 10 is opened by a biasing force of a spring 34. On the other hand, at the W/C high pressure timing, the piston 33 slides against the force of the spring 34, and therefore the first valve 10 is closed by causing the valve element 35 to rest on the valve seat

36.

Further, the second control valve 11 has first and second ports 41, 42, a piston 43, a spring 44, a valve element 45 and a valve seat 46. The valve element 45 moves in conjunction with the piston 43 and rests on the valve seat 45. The first port 41 is connected to the discharge port side of the pump 8, and the second port 42 is connected to W/C 4, 5 side. Further, the second control valve 11 has a check valve 47 that is arranged downstream (on the W/C 4, 5 side) from the first port 41 and allows the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8. Accordingly, at the W/C low pressure timing, the second control valve 11 is closed because the valve element 45 rests the valve seat 46 by a force of a spring 44. on the other hand, at the W/C high pressure timing, the piston 43 slides against the force of the spring 44, and therefore the second control valve 11 is opened by leaving the valve element 45 from the valve seat 46.

In this embodiment, the first and second control valves 10, 11 are driven mechanically based on the W/C pressure, thereby obtaining the same advantage as the first embodiment.

There is a possibility, by an error of manufacturing, that the valve positions of the first and second control valves 10, 11 cannot change at the same timing according to the change of the W/C pressure between low and high pressure. However, even if the second control valve 11 is opened later than that the first control valve 10 is closed, the brake fluid in the second chamber 9c can escape to the W/C 4, 5 side via a check valve 37, when

the W/C pressure changes low to high. On the other hand, even if the first control valve 10 is opened later than that the second control valve 11 is closed, the brake fluid on the W/C 4, 5 side can escape to the M/C 3 side via a check valve 47 and the linear valve 17.

(Third embodiment)

FIG. 8 shows a brake system of third embodiment. The first and second control valves 10, 11 are driven based on the W/C pressure in the second embodiment, but are driven based on the discharge pressure of the pump 8 in the third embodiment. The other elements of the third embodiment are similar to the second embodiment.

As shown in FIG. 9, the discharge pressure of the pump 8 is introduced to the first and second control valves 10, 11 via respective pipelines G1, G2. Specifically, the first and second control valves 10, 11 provided to the brake system as shown in FIG. 9 have valve constructions as shown in FIG. 10.

As shown in FIG. 10, the first control valve 10 has a first chamber 51, a second chamber 52, a third chamber 53, a first piston 54, a second piston 55, a spring 56, a valve element 57 and a valve seat 58. The valve element 57 moves in conjunction with the first piston 54 and rests on the valve seat 58. The first chamber 51 is connected to the second chamber 9c side of the amplifying piston 9, the second chamber 52 is connected to the W/C 4, 5 side, and the third chamber 53 is connected with the discharge port side of the pump 8. Further, the first control valve 10 has a check valve 59 that is arranged downstream (on the W/C 4, 5 side) from the first chamber 51 and allows the brake

fluid to flow only from the second chamber 9c side to the W/C 4, 5 side. Accordingly, at the W/C low pressure timing, the first valve 10 is opened by a biasing force of the spring 56. On the other hand, at the W/C high pressure timing, the first and second pistons 54, 55 slide against the force of the spring 56 because the discharge pressure communicated with the third chamber 53 becomes high, and therefore the first valve 10 is closed by causing the valve element 57 to rest on the valve seat 58.

Further, the second control valve 11 has a first port 61, a second port 62, a third port 63, a piston 64, a spring 65, a valve element 66, a valve seat 67 and a check valve 68. The valve element 66 moves in conjunction with the piston 64 and rests on the valve seat 67. The first port 61 is connected to the discharge port side of the pump 8, the second port 62 is connected to the W/C 4, 5 side via the check valve 68, and the third port 63 is connected to the W/C 4, 5 side. The check valve 68 is arranged downstream (on the W/C 4, 5 side) from the second port 62 and allows the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8. Accordingly, at the W/C low pressure timing, the second control valve 11 is closed because the valve element 66 rests on the valve seat 67 by a force of the spring 65. On the other hand, at the discharge pressure by the pump 8 is high, the piston 64 slides against the force of the spring 65, and therefore the second control valve 11 is opened by leaving the valve element 66 from the valve seat 67.

In this embodiment, the first and second control valves 10, 11 are driven mechanically depending on the discharge pressure

of the pump 8, thereby obtaining the same advantages as the first embodiment.

Moreover, if the valve position of the first and second control valves 10, 11 cannot change at the same timing according to the change of the W/C pressure between low and high pressures, the brake fluid can be escaped similarly to the second embodiment by using the check valves 59, 68.

(Forth embodiment)

FIG. 11 is showing a brake system of fourth embodiment. The first and second control valves 10, 11 are driven based on the differential pressure between the W/C pressure and the M/C pressure in this embodiment. The other elements are similar to the second embodiment.

As shown in FIG. 11, the W/C pressure and the M/C pressure are introduced to the first and second control valves 10, 11 via respective pipelines F1, F2, H1 and H2. Specifically, the first and second control valves 10, 11 provided to the brake system as shown in FIG. 11 have valve construction as shown in FIG. 12.

As shown in FIG. 12, the first control valve 10 has a first port 71, a second port 72, a third port 73, a piston 74, a spring 75, a valve element 76 and a valve seat 77. The valve element 76 moves in conjunction with the piston 74 and rests on the valve seat 77. The first port 71 is connected to the second chamber 9c side, the second port 72 is connected to the W/C 4, 5 side, and the third port 73 is connected to the M/C 3 side. Further, the first control valve 10 has a check valve 78 that is arranged downstream (on the W/C 4, 5 side) from than the first port 71

and allows the brake fluid to flow only from the second chamber 9c side to the W/C 4, 5 side. Accordingly, at the W/C low pressure timing, the first valve 10 is opened by a force of a spring 75. On the other hand, at the W/C high pressure timing, the pistons 74 slides against the force of the spring 75 based on the differential pressure between the W/C pressure and the M/C pressure, and therefore the first valve 10 is closed by causing the valve element 76 to rest on the valve seat 77.

Further, the second control valve 11 has a first port 81, a second port 82, a third port 83, a piston 84, a spring 85, a valve element 86, and a valve seat 87. The valve element 86 moves in conjunction with the piston 84 and rests on the valve seat 87. The first port 81 is connected to the discharge port side of the pump 8, the second port 82 is connected to the W/C 4, 5 side, and the third port 83 is connected to the M/C 3 side. Further, the second control valve 11 has a check valve 88 that is arranged downstream (on the W/C 4, 5 side) from the first port 81 and allows the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8. Accordingly, at the W/C low pressure timing, the second control valve 11 is closed because the valve element 86 rests on the valve seat 87 by a force of a spring 85. On the other hand, at the W/C pressure high timing, the piston 84 slides against the force of the spring 85 based on the differential pressure between the W/C pressure and the M/C pressure, and therefore the second control valve 11 is opened by leaving the valve element 86 from the valve seat 87.

In this embodiment, the first and second control valves

10, 11 are driven mechanically based on the differential pressure between the W/C pressure and the M/C pressure, thereby obtaining the same advantages as the first embodiment.

Moreover, if the valve position of the first and second control valves 10, 11 cannot change at the same timing according to the change of the W/C pressure changes between low and high pressure, the brake fluid can be escaped similarly to the second embodiment by using the check valves 78, 88.

(Fifth embodiment)

FIG. 13 shows a brake system of fifth embodiment. The first and second control valves 10, 11 are driven based on the differential pressure between the discharging pressure by the pump 8 and the W/C pressure in this embodiment. The other elements are similar to the second embodiment.

As shown in FIG. 13, the W/C pressure and the discharge pressure of the pump 8 is introduced to the first and second control valves 10, 11 via respective pipelines J1, J2, K1 and K2. Specifically, the first and second control valves 10, 11 provided to the brake system as shown in FIG. 14 have valve construction as shown in FIG. 14.

As shown in FIG. 14, the first control valve 10 has a first port 91, a second port 92, a third port 93, a fourth port 94, a piston 95, a spring 96, a valve element 97, a valve seat 98 and a check valve 99. The valve element 97 moves in conjunction with the piston 95 and rests on the valve seat 98. The first port 91 is connected to the second chamber 9c side, the second port 92 is connected to the W/C 4, 5 side via the check valve 99, the

third port 93 is connected to the W/C 4, 5 side, and the fourth port 94 is connected to the discharge port side of the pump 8. The check valve 99 is arranged downstream (on the W/C 4, 5 side) from the second port 92 and allows the brake fluid to flow only from the second chamber 9c side to the W/C 4, 5 side. Accordingly, at the W/C low pressure timing, the first valve 10 is opened by a force of a spring 96. On the other hand, at the W/C high pressure timing, the pistons 95 slides against the force of the spring 96 based on the differential pressure between the discharge pressure of the pump 8 and the W/C pressure, and therefore the first valve 10 is closed by causing the valve element 97 to rest on the valve seat 98.

Further, the second control valve 11 has a first port 101, a second port 102, a third port 103, a fourth port 104, a piston 105, a spring 106, a valve element 107, a valve seat 108 and a check valve 109. The valve element 107 moves in conjunction with the piston 105 and seats on the valve seat 108. The first port 101 is connected to the discharge port side of the pump 8, the second port 102 is connected to the W/C 4, 5 side via the check valve 109, and the third and the fourth ports 103, 104 are connected to the M/C 3 side. The check valve 109 is arranged downstream (on the W/C 4, 5 side) from the second port 109 and allows the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8. Accordingly, at the W/C low pressure timing, the second control valve 11 is closed because the valve element 107 rests on the valve seat 108 by a force of a spring 106. On the other hand, at the W/C pressure high timing, the piston

105 slides against the force of the spring 106 based on the differential pressure between the discharging pressure by the pump 8 and the W/C pressure, and therefore the second control valve 11 is opened by leaving the valve element 107 from the valve seat 108.

In this embodiment, the first and second control valves 10, 11 are driven mechanically based on the differential pressure between the discharge pressure of the pump 8 and the W/C pressure, thereby obtaining the same advantages as the first embodiment.

Moreover, if the valve position of the first and second control valves 10, 11 cannot change at the same timing according to the change of the W/C pressure changes between low and high pressure, the brake fluid can be escaped similarly to the second embodiment by using the check valves 99, 109.

(Sixth embodiment)

FIG. 15 shows a brake system of sixth embodiment. In this embodiment, the amplifying piston 9 also plays a role of the first and second control valves 10, 11 shown in FIG. 1.

Specifically, the pipeline A1 is formed from the guide wall that accommodates the large diameter portion of the step piston 9a to the W/C 4, 5 side. The pipeline A2 is formed from the guide wall that accommodates the small diameter portion of the step piston 9a to the W/C 4, 5 side. The first and second control valves 10, 11, which are shown in FIG. 1, are not provided to the brake system in this embodiment. The second chamber 9c communicates with the W/C 4, 5 side at the low W/C pressure timing, and the first chamber 9b communicates with the W/C 4, 5 side at the high

W/C pressure timing. That is, when the step piston 9a does not slide (before the discharge pressure of the pump 8 is not applied), a distance S1 is equal to or slightly longer than a distance S2. Where S1 is a distance from the most first chamber 9b side end of the facing region between the small diameter portion and the guide wall to the pipeline A2, and S2 is a distance from the most second chamber 9c side end of the facing region between the large diameter portion and the guide wall to the pipeline A1.

In this construction, the selection between the pipelines A1, A2 can be performed mechanically according to a sliding stroke of the amplifying piston 9, thereby obtaining the same advantages as the first embodiment.

The second chamber 9c is connected to the W/C 4, 5 via pipeline A5 provided in the brake system aside from the pipeline A2. A check valve 110 is employed in the pipeline A5, thereby allowing the brake fluid to flow only from the second chamber 9c side to the W/C 4, 5 side. Accordingly, even if the pipeline A1 is closed before the pipeline A2 is opened due to by an error of manufacturing, the brake fluid in the second chamber 9c can be escaped to the W/C 4, 5 side via a check valve 110.

(Seventh embodiment)

FIG. 16 shows brake system of seventh embodiment. In this embodiment, the amplifying piston 9 also plays a role of the first and second control valves 10, 11 shown in FIG. 1 similarly to sixth embodiment.

Specifically, the pipeline A2 is formed to connect the first chamber 9b to the W/C 4, 5. The amplifying piston 9 has a valve

element (a second valve element) 9h, a valve seat (a second valve seat) 9i, a valve element (a first valve element) 9j, a spring 9k, and a valve seat (a second valve seat) 9m. The valve element 9h is arranged at the large diameter portion. It moves in conjunction with the step piston 9a and rests on the valve seat 9i. The valve element 9j is arranged in the small diameter portion and is pushed toward the valve seat 9m by a force of a spring 9k. A lift amount S3 of the valve element 9j is equal to or slightly longer than a lift amount S4 of the valve element 9h.

In this construction, at the low W/C pressure timing, the second chamber 9c can communicate with the W/C 4, 5 side via the pipeline A1. Then, if the pump 8 discharges the brake fluid, the step piston 9a slides upward in FIG. 16. However, the valve element 9j is pushed in an opposite direction to the movement of the step piston 9a and rests on the valve seat 9m. Thus, the pipeline A2 maintains to be closed. Next, at the high W/C pressure timing, the valve element 9j leaves from the valve seat 9i and the valve element 9h rests on the valve seat 9i. Therefore, the pipeline A1 is controlled to a close condition, and the pipeline A2 is controlled to an open condition.

In this embodiment, the selection between the pipelines A1, A2 can be performed mechanically according to the sliding movement of the amplifying piston 9, thereby obtaining the same advantages as the sixth embodiment.

(Eighth embodiment)

FIG. 17 shows a brake system of eighth embodiment. In this embodiment, the different construction from the sixth or the

seventh embodiment plays a role of the first and second control valves 10, 11 shown in FIG. 1.

Specifically, a restriction orifice 121 is provided between the discharge port side of the pump 8 and the first chamber 9b.

Further, a bypass valve 122, which is driven based on the differential pressure between both sides of the restriction orifice 121, is employed in the pipeline A2. The bypass valve 122 has a first port 122a, a second port 122b, a third port 122c, a piston 122d, a spring 122e, a valve element 122f, and a valve seat 122g. The valve element 122f moves in conjunction with the piston 122d and rests on the valve seat 122g. The first port 122a is connected to the pipeline A1 between the restriction orifice 121 and the pump 8, the second port 122b is connected to the pipeline A1 between the restriction orifice 121 and the amplifying piston 9, and the third port 122c is connected to the W/C 4, 5. In this construction, if the discharge amount from the pump 8 is large and the differential pressure is generated between both sides of the restriction orifice 121, the piston 122d slides downstream (on the W/C 4, 5 side). Accordingly, the seat valve 122f rests on the valve seat 122g, thereby closing the pipeline A2.

In this embodiment, the selection between the pipelines A1, A2 can be performed mechanically depend on the pressure difference generated by the restriction orifice 121, thereby obtaining the same advantages as the sixth or the seventh embodiment.

In this construction, if the discharge amount from the pump 8 is not large, the pipeline A2 is opened. In this case, the

discharge pressure by the pump 8 directly pressurizes the W/C 4, 5. However, it is not problem because the high pressurize response is not required under this condition.

(Ninth embodiment)

5 FIG. 18 shows a brake system of ninth embodiment. In this embodiment, the connection position with the third chamber 9g is modified from that of the first embodiment. Specifically, the third chamber 9g is provided with an atmosphere pressure or is connected with master reservoir 3a under the atmosphere pressure.

10 This construction forbids the brake fluid to flow from the M/C 3 side to the third chamber 9g. As a result, the brake fluid amount flowing from the M/C 3 is limited, and therefore a small capacity M/C can be employed as the M/C 3. Further, a body of the M/C 3 can be miniaturized. Accordingly, the stroke amount of the brake pedal 2 can be shorten, and reactive force of the
15 brake pedal 2 can be reduced. Therefore, required pressure for operating the pedal by a driver during a malfunction of an electrical system or pressure source can be reduced. Moreover, the second control valve 11 and the linear valve 17 are of normally open
20 type. Accordingly, the pressurizing amount of the W/C pressure can be enlarged in response to the pedal pressure to the brake pedal 2 due to a small size of the diameter of the M/C 3.

(Tenth embodiment)

25 FIG. 19 shows a brake system of tenth embodiment. In this embodiment, the position of the linear valve 17 is modified from the first embodiment. Specifically, the linear valve 17 is positioned in a pipeline between the M/C 3 and the pressurization

control valves 13, 14.

In this construction, the differential pressure between the W/C pressure and the M/C pressure is controlled by adjusting the duty ratio of the current to the linear valve 17, thereby
5 controlling the W/C pressure more directly.

(Eleventh embodiment)

FIG. 20 shows a brake system of eleventh embodiment. In this embodiment, the position of the linear valve 17 is modified from the sixth embodiment. Specifically, the linear valve 17 is positioned in a pipeline between the M/C 3 and the pressurization control valves 13, 14.

Further, a spool leak occurs from the first chamber 9b to the pipeline A2 through a clearance between the small diameter portion of the step piston 9a and the guide wall or the like. If the linear valve is positioned between the discharge port side of the pump 8 and the M/C 3 as in the first embodiment, a relief leak occurs through the liner valve and the pressure regulating reservoir 6 or the like. Therefore, the step piston 9a never reach the limit (i.e., upper wall). However, if the linear valve 17
15 is positioned at the above-mentioned position, the step piston 9a sometimes reaches the limit since there is no relief leak. Accordingly, the spool leak is formed in this embodiment.

In this embodiment, the selection between the pipelines A1, A2 can be performed mechanically by the amplifying piston 9, and, further, the W/C pressure may be pressurized more directly
25 as in the tenth embodiment. Moreover, since the spool leak decrease the discharge amount from the pump 8, the W/C pressure

may be pressurized via the pipeline A2 at the normal braking timing in which high pressurization is not required at no urgent control timing. In this case, the stroke of the amplifying piston 9 is suppressed.

5 (Twelfth embodiment)

FIG. 21 shows a brake system of twelfth embodiment. This embodiment is a modification of the eleventh embodiment and the selection between the first and second pipelines A1, A2 is performed by the restriction orifice 121 and the bypass valve 122 as in the eighth embodiment. The restriction orifice 121 and the bypass valve 122 operate as the eighth embodiment. This structure can obtain the same advantages as the eleventh embodiment.

(Thirteenth embodiment)

FIG. 22 shows a brake system of thirteenth embodiment. In this embodiment, a three ports-two position valve 131 is employed instead of the first and second control valves 10, 11 shown in FIG. 1. In the valve 131, when one position is selected, the pipeline A1 is opened and the pipeline A2 is closed. To the contrary, when the other position is selected, the pipeline A1 is closed and the pipeline A2 is opened. A check valve 132 is employed between the second chamber 9c and the W/C 4, 5 to permit the brake fluid to flow only from the second chamber 9c to the W/C 4, 5 side.

In this construction, the three ports two position valve 131 is driven and controlled by the brake control ECU 1 as shown in the first embodiment. Further, it is easier to bleed air from the brake piping in this embodiment.

(Fourteenth embodiment)

FIG. 23 shows a brake system of fourteenth embodiment. In this embodiment, a three port two position mechanical valve 133 is employed instead of the first and second control valves 10, 11 shown in FIG. 1.

5 The valve 133 has a first port 133a, a second port 133b, a third port 133c, a piston 133d, a spring 133e, and pipeline 133f. The first port 133a is connected to the second chamber 9c, the second port 133b is connected to the discharge port side of the pump 8, and the third port 133c is connected to the W/C 4, 5 side. The piston 133d slides against a force of the spring 133e by the W/C pressure applied thereto through the pipeline 133f.

10 In this construction, at the low W/C pressure timing, the pipeline A1 is opened and the pipeline A2 is closed. To the contrary, at the high W/C pressure timing, the pipeline A1 is closed and the pipeline A2 is opened. Therefore, the brake system obtains the same advantages as the first embodiment.

15 (Fifteenth embodiment)

FIG. 24 shows a brake system of fifteenth embodiment. This brake system is mounted on the vehicle, such as an electric vehicle, 20 having regenerative brake equipment. The basic constitution of the brake system including the brake piping and sensors is basically the same as the first embodiment.

As shown in FIG. 24, the pressure increase to respective W/C 4, 5 may be controlled by the regenerative motor 142, which 25 is driven by the regenerative control ECU 141. The regenerative control ECU 141 exchanges information with the brake control ECU 1. The W/C pressure can be regulated by duty controlling the

depressurization control valve 15 that is a linear valve. The differential pressure between the brake pressure at a position of the W/C pressure sensor 20 and real W/C pressure is regulated by duty controlling the pressurization linear valve 143.

5 The brake system with the regenerative brake equipment has the same advantages as the first embodiment. In the brake system of this embodiment, the discharge pressure of the pump 8 is regulated in use of a brake flow path passing through the linear valve 17 and the pressure regulating reservoir 6, when a cooperative control with the regenerative braking is not executed (See an arrow T shown in FIG. 24). On the other hand, the depressurization control valve 15 is controlled by duty control, when a cooperative control with the regenerative braking is executed so that the discharge pressure of the pump 8 is regulated in use of a brake flow path passing through the second control valve 11, the pressurization linear valve 143, the pressurization control valve 13 and the depressurization control valve 15 (See arrows U1-U3 shown in FIG. 24).

(Sixteenth embodiment)

20 FIG. 25 shows a brake system of sixteenth embodiment. This brake system is mounted on the vehicle whose respective wheels have liner control units. The basic constitution of this brake system is basically the same as the first embodiment.

25 As shown in FIG. 25, respective control valves 13-16, which are linear valves, are controlled by duty control. As a result, the W/C pressure is regulated with respect to the individual wheel (individual wheel brake pressure control).

This brake system, which is controlled by the respective wheel brake pressure control, has the same advantages as the first embodiment. In the brake system of this embodiment, the discharge pressure of the pump 8 is regulated in use of a brake flow path passing through the linear valve 17 and the pressure regulating reservoir 6, when the individual wheel brake pressure control is not executed (See an arrow V shown in FIG. 25). On the other hand, each of the control valves 13-16 is controlled by duty control, when the individual wheel brake pressure control is executed. Therefore, the discharging pressure by the pump 8 is regulated in use of a brake flow path passing through the second control valve 11 and the respective control valves 13-16 (See arrows W1-W5 shown in FIG. 25).

(Seventeenth embodiment)

FIG. 26 shows a brake system of seventeenth embodiment. In this embodiment, a brake piping similar to the first embodiment is employed as a brake pressure generating source of a brake system having EHB or active hydro booster or the like.

As shown in FIG. 26, the brake system of this embodiment has a brake pedal 201, a M/C 202, master reservoir 202a, and W/C 203-206 that are provided for respective wheels. These elements have the same construction as the first embodiment.

The M/C 202 is connected to front side W/C 203, 204 via a pipeline L1. The M/C 202 is connected rear side W/C 205, 206 via a pipeline L2. The pipelines L1, L2 are provided with two position valves 207, 208 that control open or close condition between the M/C 202, the W/C 203-206, two position valve 209 that

controls the open or close condition between both of the front side W/C 203, 204, and two position valve 210 that controls the open or close condition between both of the rear side W/C 205, 206.

5 A pipeline L3 is connected to the pipeline L1 between the M/C 202 and the two position valve 207. In this pipeline L3, a stroke simulator 211 and a two position valve 212 are provided. The two position valve 212 controls the brake fluid flow to the stroke simulator 211.

10 Further, the master reservoir 202a is connected to
15 respective W/C 203-206 via a pipeline M. This pipeline M plays
a role of the pipeline A of the first embodiment. The same
construction as the first brake piping of the first embodiment
is provided in this pipeline. Namely, the motor 7, the pump 8,
the amplifying piston 9, the first and second control valves 10,
11, the pressurization control valves 13, 14, and the
depressurization control valves 15, 16 are provided. However,
the pressurization control valves 13', 14', and the
depressurization control valves 15', 16' are provided downstream
20 from the first and second control valves 10, 11 via a pipeline
A' so that the W/C 205, 206 of the second brake piping can be
controlled based on the discharge pressure of the pump 8. The
control valves 13'-16' play roles of the control valves 13-16.
Linear valves are employed as the control valves 13-16, 13'-16'
25 in this embodiment.

Moreover, the master reservoir 202a is connected to the discharge port side of the pump 8 via a pipeline N. A relief valve

213 is provided in the pipeline N, thereby controlling the open or close condition of the pipeline N based on the differential pressure between the discharge pressure of the pump 8 and the brake fluid pressure of the master reservoir 202a (i.e., atmosphere pressure).

Respective brake pressure of the pipelines can be detected by respective sensors 214-221. Specifically, the discharge pressure of the pump 8 is detected by a pressure sensor 214. The brake pressure between the first or second control valves 10, 11 and each of the pressurization control valves 13, 14, 13', 14' is detected by a pressure sensor 215. Respective W/C pressures are detected by respective pressure sensors 216-219. The pedal pressure (pedal condition) of the brake pedal 201 is detected by a pedal pressure sensor 222.

In this brake system, when the brake pedal 201 is depressed, the brake fluid in the master reservoir 202a is provided to the W/C 203-206 by the pump 8. Therefore, the W/C pressure corresponding to the pedal pressure is generated. That is, the W/C pressure is not pressure depending on the M/C pressure.

Specifically, when the brake pedal 201 is depressed, the two position valves 207, 208 are closed so as not to transmit the M/C pressure to the W/C 203-206. Moreover, the two position valve 212 is opened so that the stroke simulator 211 can reserve the brake fluid from M/C 202. Further, the pump 8 sucks the brake fluid based on the pedal pressure of the brake pedal 201 from the master reservoir 202a, and discharges it to the W/C 203-206 sides. Then, the duty ratio of the current to each of the linear

valves 13-16, 13'-16' is adjusted. Therefore, desired W/C pressure is generated at each W/C 203-206.

In this construction, the selection between the pipelines A1, A2 can be performed by the first and second control valves 10, 11, thereby obtaining the same advantages as the first embodiment.

The present brake system may employ not only the brake piping of the first embodiment but also the brake piping of any of the second to sixteenth embodiments.

(Eighteenth embodiment)

FIG. 27 shows a brake system of eighteenth embodiment. In this embodiment, port connecting positions of the amplifying piston 9 is modified from the second embodiment. Specifically, the first chamber 9b is connected to the M/C 3 side, and the third chamber 9g is connected to the discharge port side of the pump 8. Namely, these connecting positions are opposite to those of the second embodiment, thereby obtaining the same advantages as the second embodiment. Further, this construction serves to easily set a larger amplification ratio of the amplifying piston 9.

(Nineteenth embodiment)

FIG. 28 shows a brake system of nineteenth embodiment. In this embodiment, the communication condition of the third chamber of the amplifying piston 9 in the first brake piping or the like is modified from the sixth embodiment. Specifically, a check valve 301 that allows the brake fluid to flow only from the M/C 3 side to the third chamber 9g side is provided in the pipeline C. The

check valve 302 that allows the brake fluid to flow only from the amplifying piston 9 side to the W/C 4, 5 side is provided in the pipeline A2. Further, a pipeline O that connects the discharge port side of the pump 8 to the W/C 4, 5 is provided, and a check valve 303 that allows the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8 instead of the check valve 100 shown in FIG. 15.

In this case, when the pipeline A2 is opened according to the slide of the amplifying piston 9, the pressure in the third chamber 9g is changed from the M/C pressure to the discharge pressure of the pump 8. The force for pushing the amplifying piston 9 toward the W/C 4, 5 side increases. As a result, a distance between the opening of the pipeline A2 and the end of the amplifying piston is secured to a desired level. Accordingly, the brake fluid discharged from the pump 8 flows into the W/C 4, 5 with less flow resistance. The other operations are the same as the sixth embodiment.

This structure obtains the same advantages as the sixth embodiment.

(Twentieth embodiment)

FIG. 29 shows a brake system of twentieth embodiment. In this embodiment, similarly to the sixth embodiment, the amplifying piston 9 plays a role of the first and second control valves 10, 11 shown in FIG. 1.

Specifically, a spool valve unit 401 is provided in the guide wall that accommodates the small diameter portion of the step piston 9a. Moreover, the third chamber 9g is connected to

the W/C 4, 5 side so that the pipeline A2 is formed by a path through the spool valve unit 401 and the third chamber 9g.

A check valve (a first check valve) 402 is provided in the pipeline A2 between the third chamber 9g and the W/C 4, 5 so as to permit the brake fluid to flow only from the third chamber 9g to the W/C 4, 5 side. The pipeline A2 downstream (on the W/C 4, 5 side) from the check valve 402 connected to the discharge port side of the pump 8 via a pipeline P1, which constitutes to a feedback path. A check valve (a second check valve) 403 is provided in the pipeline P1 to permit the brake fluid to flow only from the W/C 4, 5 side to the discharge port side of the pump 8.

Moreover, the third chamber 9g is connected to the M/C 3 side via a pipeline P2. A check valve (a third check valve) 404 is provided in the pipeline P2 to permit the brake fluid to flow only from the M/C 3 side to the third chamber 9g.

With this constitution, the spool valve unit 401 is opened or closed according to the slide of the step piston 9a. That is, the spool valve unit 401 is opened when the end of the step piston 9a reaches a position of the spool valve unit 401. Then, the W/C 4, 5 is pressurized via the pipeline A2 through the spool valve unit 401 and the third chamber 9g. As the check valve 403 is provided in the pipeline P1, the discharge pressure of the pump 8 does not transmit to the W/C 4, 5 through the pipeline P1.

When the pressurizing path is switched from the pipeline A2 to the pipeline A1 when the spool valve unit 401 is closed by the step piston 9a, the brake fluid that is provided to the

W/C 4, 5 side via the pipeline A2 is returned via the pipeline P1. In this way, the selection between the pipelines A1, A2 can be performed mechanically based on the sliding movement of the amplifying piston 9. This embodiment obtains the same advantages as the first embodiment.

If the detecting result of the pedal pressure sensor 18 requires to promote a deceleration of the vehicle, the differential pressure between both sides of the linear valve 17 is regulated so that the discharge pressure of the pump 8 is a required W/C pressure multiplied by pressure-receiving surface ratio of the step piston 9a. On the other hand, the detecting result requires to maintain or reduce the deceleration, the differential pressure between both sides of the linear valve 17 is regulated so that the discharging pressure by the pump 8 is the same pressure as the required W/C pressure.

As mentioned above, the brake pressure in the third chamber 9g becomes to the discharge pressure of the pump 8, when the spool valve unit 401 communicates with the third chamber 9g, so that a differential pressure is generated between the third chamber 9g and the M/C 3 side. However, since the check valve 404 is provided in the pipeline P2 between the third chamber 9g and the M/C 3 side, the brake flow from the third chamber to the M/C 3 side is forbidden.

Moreover, preferably before the spool valve unit 401 becomes open, the high brake pressure generated in the second chamber 9c should not be applied to the third chamber 9g, since the step piston 9a should be operated only by the differential pressure

between the first chamber 9b and the second chamber 9c. Therefore, the check valve 402 is provided in the pipeline A2 between the third chamber 9g and the W/C 4, 5 so that the high brake pressure generated in the second chamber 9c cannot be supplied to the third chamber 9g.

In this embodiment, the spool valve 401 is connected to the third chamber 9g. However, this constitution is not essential, and the spool valve unit 401 may be connected to the W/C 4, 5 side in such a manner that the pipeline A2 does not pass through the third chamber 9g. However, the twentieth embodiment has the following advantages.

The W/C 4, 5 are pressurized directly by the discharge pressure of the pump 8 via the pipeline A2 when the spool valve unit 401 is opened and the pipeline A2 is selected as the pressurizing path. However, according to an experimental test result, if the pipeline A does not pass through the third chamber 9g, there likely occurs that the spool valve unit 401 repeats open and close operation continuously so that the brake pressure in the first chamber 9b is higher than that of the second chamber 9c, if this effect occurs the selection between the pipelines A1, A2 is not stable. In order to avoid this unstable condition, the spool valve unit 401 is connected to the W/C 4, 5 side through the third chamber 9g in this embodiment.

(Twenty-first embodiment)

FIG. 30 shows a brake system of twenty-first embodiment. This brake system is modified from the first embodiment so as to cooperate with the regenerative braking. Specifically, the

second control valve (a first liner control valve) 11 and the depressurization control valve (a second linear valve) 15 are linear valves and the third chamber 9g is connected to the master reservoir 3a under to the atmosphere pressure.

5 When the cooperation control with the regenerative braking is executed, the pressure to be compensated by the regenerative braking is reduced from the W/C pressure to be estimated based on the pedal pressure of the brake pedal 2. Accordingly, in this embodiment, the linear valve 15 serves to decrease the W/C pressure appropriately. An instruction signal for generating the differential pressure by the second control valve 11 is synchronized with the control signal for driving the linear valve 17 so as not to shift the differential pressure between the first chamber 9b and the second chamber 9c. Therefore, the valve open and close operation of the second control valve 11 control to return the brake fluid to be compensated by the regenerative braking to the second chamber 9c.

10
15
20 Accordingly, the capacity change of the W/C 4, 5 during the cooperation control with the regenerative braking is absorbed by adjusting the difference of capacity change between the first chamber 9b and the second chamber 9c so that the shift of brake pedal 2 may be limited.

25 On the other hand, when the regenerative braking is stopped, the W/C pressure has to increase by the pressure due to the regenerative braking. Accordingly, the linear valve 17 serves to increase the W/C pressure appropriately. In this case, an instruction signal for generating the differential pressure by

the second control valve 11 is synchronized with the control signal for driving the linear valve 17.

In this way, when the pressure change due to the regenerative braking is reduced from the W/C pressure, the step piston 9a is controlled so as to return toward its initial position than the case when the regenerative braking is not executed. To the contrary, when the pressure change due to the regenerative braking is increased from the W/C pressure, the step piston 9a is controlled so as to push toward its advanced position than the case when the regenerative braking is executed. Therefore, the cooperation control with the regenerative braking can be executed appropriately. Moreover, a driver does not have uncomfortable feeling based on the shift of the brake pedal 2 because the capacity change of the W/C 4, 5 is absorbed by the amplifying piston 9.

(Twenty-second embodiment)

FIG. 31 showing a brake system of twenty-second embodiment. The brake system in this embodiment executes a cooperation control with the regenerative braking with a construction different from the twenty-first embodiment.

Specifically, the brake system in this embodiment does not have the first control valve 10 shown in FIG. 30. The second chamber 9c is connected to the M/C 3 side via the check valve 12. The second pipeline A2 with the second control valve 11 is connected between the discharge port side of the pump 8 and a pipeline D1 between the depressurization control valve 15 and the W/C 4. Moreover, the third chamber 9g is connected to the master reservoir 3a.

This brake system is operated similarly to the twenty-first embodiment and the depressurization control valve 15 and the second control valve 11, which are the linear valves, are driven so that the cooperative control with the regenerative braking can be executed.

The brake fluid is applied to the third chamber 9g from the master reservoir 3a. Therefore, the brake fluid from the M/C 3 is supplied only to the first chamber 9b. Accordingly, the W/C 4, 5 can be pressurized by small amount of the brake fluid from the M/C 3, and a diameter of the M/C 3 can be miniaturized.

Moreover, if the respective control valves 11, 13-17 and the motor 7 do not work during a malfunction of an electrical system, the W/C 4 can be pressurized via a path through the M/C 3, the linear valve 17, the second control valve 11 and the W/C 4. The W/C 5 can be pressurized via a path through the M/C 3, the linear valve 17, the second control valve 11, the pressurization control valves 13, 14 and the W/C 5. In this case, even if the diameter of the M/C 3 is small, a pressurizing amount amplifying ratio to pedal pressure of the brake pedal 2 is large.

According to this embodiment, only the W/C 4 can be directly pressurized by the pump 8 or be depressurized through the second control valve 11 at the high pressure timing. Accordingly, the W/C 4 is preferably applied to the front wheels.

That is, the pipeline A2 is not connected to the W/C 5 side, but connected to the W/C 4 side. Therefore, the brake fluid is mainly provided to the W/C 4 side. Accordingly, in order to mainly supply the brake fluid to the front wheel side that requires more

high pressure than the rear wheel side, it is preferable that the W/C 4 is applied to the front wheel. In this case, the W/C 5 that is applied to the rear wheel side cannot be pressurized after the pipeline A2 is selected as the pressurizing path, but it is not necessary to increase the brake pressure of the rear wheel already generated when the pipeline A1 is selected as the pressurizing path.

Further, the front wheel side is likely to make noises, and governs mainly the brake fluid pressure control. Accordingly, the noises can be reduced sufficiently and the brake pressure control can be executed smoothly by controlling the W/C 4 with the second control valve 11 and depressurization control valve 15.

(Twenty-third embodiment)

FIG. 32 shows a brake system of twenty-third embodiment. This brake system is modified from the first embodiment so as to cooperate with the regenerative braking. Specifically, a stroke simulation piston (SS piston) 410 for absorbing the shift of the brake pedal 2 is provided to the brake piping. The third chamber 9g is connected to the master reservoir 3a and not connected to the M/C 3. As a result, the diameter of the M/C 3 is miniaturized similarly to the twenty-second embodiment. Further, the first control valve 10 is of a normally closed type. The pipeline B connecting between the second chamber 9c and the M/C 3 side, and the check valve 12 (See FIG. 1) in the first embodiment are not provided.

As shown in FIG. 32, SS piston 410 has a piston portion

(the second step piston) 411, a first chamber 412, a second chamber 413 and a spring 414. The first and second chambers 412, 413 are formed by the piston portion 411 and its guide wall. In the SS piston 410, the first chamber 412 is connected to the pipeline A1 between the amplifying piston 9 and the first control valve 10, and the second chamber 413 is connected to the M/C 3 side. Accordingly, the SS piston 410 is operated based on the differential pressure between the W/C pressure and the M/C pressure.

A pressure-receiving surface of the piston portion 411, which is exposed to the M/C pressure, is larger than that exposed to the W/C pressure. The piston portion 411 is pushed toward the M/C 3 side by the spring 414. Therefore, the piston portion 411 is located at the most M/C 3 side when the M/C pressure is not generated. The biasing force of spring 414 is stronger than that of an usual simple return spring to an extent that while a given relationship between the brake pressure of the first chamber 412 and that of the second chamber 411 is maintained, the piston portion 411 can slide on the guide wall. A chamber formed by the stepped portion of the piston portion 411 and the guide wall is provided with an atmosphere pressure air or is connected to the master reservoir 3a under the atmosphere pressure.

In this construction, the pipeline A1 is selected as the pressurizing path at the W/C low pressure timing, and the W/C 4, 5 are pressurized by the amplifying piston 9. When the brake fluid due to the regenerative braking is escaped via the linear valve 17 by cooperation control with the regenerative braking, the differential pressure between the W/C pressure and the M/C

pressure is decreased, and the escaped brake fluid is reserved in the second chamber 9c. Therefore, the shift of the brake pedal 2 can be absorbed since the second chamber 9c serves to prevent the brake fluid due to the regenerative braking from feedbacking to the M/C 3. Moreover, a pushing back of the brake pedal 2 due to the feedback of the brake fluid to the M/C 3 is suppressed.

The brake fluid to be escaped at the regenerative braking can be reserved in the second chamber 413 by adequately setting a pressure-receiving surface ratio of large diameter portion to the small diameter portion of the piston portion 411 and a spring constant of the spring 414.

On the other hand, the pipeline A2 is selected as the pressurizing path at the W/C high pressure timing, and the W/C 4, 5 are pressurized by the discharge pressure of the pump 8 directly. The amplifying piston 9 and the SS piston 410 do not work because the first control valve 10 is closed. In this case, the W/C 4, 5 are pressurized by the path through the M/C 3, the linear valve 17, the second control valve 11, the W/C 4, 5. As mentioned-above, even if the diameter of the M/C 3 is smaller, the ratio of pressurizing amount to pedal pressure of the brake pedal 2 is larger.

(Twenty-fourth embodiment)

FIG. 33 shows a brake system of twenty-fourth embodiment. This brake system is modified from the first embodiment so as to cooperate with the regenerative braking.

Specifically, an amplifying piston 420 is provided in the brake piping, and a third reservoir port 6f is formed at the pressure

regulating reservoir 6. The third reservoir port 6f is connected to the first reservoir port 6a via a linear valve 421. A check valve 422 is employed between the third chamber 9g and the M/C 3 to permit the brake fluid to flow only from the M/C 3 side to the third chamber 9g. Moreover, the second control valve 11 is of normally closed valve. The third chamber 9g is connected to the pipeline A2 between the discharge port of the pump 8 and the second control valve 11 via the check valve 423. The check valve 423 allows the brake fluid to flow only from the third chamber 9g to the pipeline A2 side. The control valve 10, which is provided in the first embodiment, is not provided, and the second chamber 9c is not connected to the M/C 3.

As shown in FIG. 33, the amplifying piston 420 has a piston portion (a second step piston) 424, a first chamber 425, a second chamber 426 and a spring 427. The first and second chamber 425, 426 are formed by the piston portion 424 and its guide wall. In this amplifying piston 420, the first chamber 425 is connected to the pipeline A1 between the amplifying piston 9 and the pressurization control valves 13, 14, and the second chamber 426 is connected to the M/C 3 side. This amplifying piston 420 is operative based on a difference between the W/C pressure and the M/C pressure.

The piston portion 424 has a small diameter portion that is pushed by the W/C pressure and a large diameter portion that is pushed by the M/C pressure. The piston portion 424 is biased toward the M/C 3 side by the spring 427. Therefore, the piston portion 424 is located at the most M/C 3 side when the M/C pressure

is not generated. The biasing force of spring 414 is as large as a simple return spring. A chamber formed by the stepped portion of the piston portion 424 and the guide wall is provided with an atmosphere pressure air or is connected to the master reservoir 3a under to the atmosphere pressure.

In this construction, the pipeline A1 is selected as the pressurizing path at the W/C low pressure timing and at the urgency braking, so that the second control valve 11 is closed. On the other hand, the second control valve 11 is opened at the W/C high pressure timing, so that the W/C 4, 5 are pressurized by the discharge pressure of the pump 8. Therefore, both the discharge pressure of the pump 8 and the pedal pressure of the brake pedal 2 are used effectively for pressurizing the W/C 4, 5.

Further, when the cooperation control with the regenerative braking is executed, the amplifying piston 9 is not used. In this case, while the second control valve 11 is opened, the W/C pressure is rated by driving the linear valve 17. The linear valve 421 is driven appropriately, the reduced brake fluid due to the regenerative braking can be escaped to the pressure regulating reservoir 6 via an arrow path shown in FIG. 33. Therefore, the shift of the brake pedal 2 is suppressed.

(Twenty-fifth embodiment)

FIG. 34 shows a brake system of twenty-fifth embodiment. This brake system is modified from the twentieth embodiment, so that an effective diameter of the M/C 3 is variable to improve the brake efficiency at the malfunction of an electrical system.

As shown in FIG. 34, the M/C 3 has a cylindrical housing

3b, small diameter pistons 3c, 3d and a large diameter piston 3e. The small diameter pistons 3c, 3d are accommodated in the housing 3b and slides on the guide wall constituting the inner wall of the housing. They are linked with each other. The large
5 diameter piston 3e, whose diameter is larger than that of the small diameter pistons 3c, 3d, acts as an input piston.

The small diameter pistons 3c, 3d are a primary piston and a secondary piston respectively. A primary chamber 3f is formed between both of the small diameter pistons 3c, 3d, and a secondary chamber 3g is formed between the small diameter piston 3c and the end wall of the housing 3b. The primary chamber 3f is connected to the first brake piping, and the secondary chamber 3g is connected to the second brake piping. Moreover, both of the primary and secondary chambers 3f, 3g communicate with the master reservoir 3a before the small diameter pistons 3c, 3d are operated, and do not communicate with the master reservoir 3a after the small diameter pistons 3c, 3d are operated.

Further, there are two chambers 3h, 3i on opposite sides of the large diameter piston 3e. One of the chambers is a ratio change chamber 3h that is located on a side of the small diameter pistons 3c, 3d side so as to surround a circumference of the small diameter piston 3c. The other chamber 3i is located on a side of the brake pedal 2 and is connected to the master reservoir 3a. The ratio change chamber 3h and the chamber 3i are connected
20 to each other via a pipeline Q1. A switching valve 430 is employed in the pipeline Q1. The pipeline Q1 is opened or closed by the
25 switching valve 430. The switching valve 430 is of a normally

open valve and is set to the position shown in FIG. 34 when its solenoid is not energized.

The chamber 3i is connected to the intake port side of the pump 8 via a pipeline Q2. The pipeline Q2 is connected to the pipeline Q1 between the switching valve 430 and the chamber 31. A check valve 431 is employed in the pipeline Q2 and allows the brake fluid to flow only from the ratio change chamber 3h and the chamber 3i to the discharge port side of the pump 8.

Further, a control valve 432 is employed in the pipeline A. The control valve 432 is located between the intake port of the pump 8 and the second reservoir port 6b of the pressure regulating reservoir 6, and is located on a side of the regulating reservoir 6 with respect to the connecting position between the pipeline A and the pipeline Q2.

The control valve 432 controls open and close conditions of the pipeline A. With this construction, either a path or the pressure regulating reservoir 6 side or a path on the master reservoir 3a side through the chamber 3i is selected for sucking the brake fluid to the pump 8.

When the cooperation control with the regenerative braking is not executed, the switching valve 430 is closed and the control valve 432 is opened. Then, if the driver pushes the brake pedal 2, the large diameter piston 3e is pushed so as to generate the brake pressure in the ratio change chamber 3h according to the pedal pressure of the brake pedal 2. Moreover, the small diameter piston 3c is moved by this brake pressure. The small diameter piston 3c move so as to be separated little by little from the

large diameter piston 3e because the diameter of the small diameter piston 3c is smaller than that of the large diameter piston 3e. Accordingly, the brake fluid pressures of the primary and the secondary chambers 3f, 3g are pressurized by the small diameter
5 pistons 3c, 3d, so that the W/C 4, 5 is pressurized, even if a diameter of the M/C 3 is small. The selection of the pressurizing path in this case is same as the twentieth embodiment.

Further, when the cooperation control with the regenerative braking is executed, the switching valve 430 and the control valve 432 are opened or closed selectively. Then, if the driver pushes the brake pedal 2, the large diameter piston 3e is pushed based on the pedal pressure of the brake pedal 2. However, while the switching valve 430, as a linear valve, controls the differential pressure between both sides thereof, the brake fluid in the ratio change chamber 3h is escaped through the pipeline Q1, the chamber 3i, and the master reservoir 3a so that the brake fluid pressure in the ratio change chamber 3h is regulated. Accordingly, the small diameter piston 3c moves toward the large diameter piston 3e side, and the M/C pressure is lowered, compared to the case
15 that the cooperation control with the regenerative braking is not executed.

When the regenerative braking is stopped, the W/C pressure is increased again. Then, if the control valve 432 are opened or closed from time to time, the brake fluid may be supplied from
25 the master reservoir 3a side to the W/C 4, 5 side via the chamber 3i and the pipelines Q1, Q2. Therefore, the W/C pressure is increased to the same pressure as when the cooperation control

with the regenerative braking is not executed. The brake fluid reserved in the pressure regulating reservoir 6 is preferentially sucked by the pump 8. Accordingly, an excessive brake fluid is not sucked from the master reservoir 3a.

5 Moreover, the switching valve 430 is opened at a malfunction of an electrical system, and, therefore, the brake fluid in the ratio change chamber 3h is escaped according to the operation of the large diameter piston 3e. Accordingly, the reactive force of the brake pedal 2 is not generated by the brake fluid pressure in the ratio change chamber 3h. It follows that the large diameter piston 3e directly pushes the small diameter piston 3c, thereby generating the M/C pressure. As a result, W/C 4, 5 can be pressurized by the small diameter M/C 3, thereby obtaining the same advantages as the twenty-third embodiment.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
1

unit 440 is connected to the third chamber 9g, and the spool valve unit 441 is connected to the fourth chamber 9n. Further, the fourth chamber 9n is connected to the W/C 4, 5 side, and, therefore, the pipeline A2 is formed by a path through the spool valve unit 440, the third chamber 9g, the spool valve unit 441 and the fourth chamber 9n.

In the pipeline A2, a check valve 442 is provided between the fourth chamber 9n and the W/C 4, 5 to allow the brake fluid to flow only from the fourth chamber 9n to the W/C 4, 5 side. The pipeline A2 downstream from the check valve 442 is connected to the discharge port of the pump 8 via a pipeline R1, which constitutes a second feedback path. A switching valve 443 is provided in the pipeline R1. The pipeline R1 is opened as necessary to play a role of the pipeline A2 so that the W/C 4, 5 is directly pressurized by the discharging pressure by the pump 8 via the pipeline R1.

Moreover, the third and the fourth chamber 9g, 9n are connected to the M/C 3 side via the pipelines C1, C2. Each of check valves 444, 445 is provided in each of the pipelines C1, C2 to allow the brake fluid to flow only from the M/C 3 side to each of the third and the fourth chambers 9g, 9n sides. A pipeline R2, which constitutes a second feedback path, is provided to connect the third and the fourth chambers 9g, 9n to the discharge port side of the pump 8. The pipeline R2 is connected between the pipeline C1 between the check valve 444 and the third chamber 9g and the discharge port of the pump 8, a check valve 446 is provided between its connected point and, a check valve 447 is

provided between its connected point and the fourth chamber 9n. The check valves 446, 447 allow the brake fluid to flow only from the third or the fourth chamber 9g, 9n side to the discharge port side of the pump 8.

5 Moreover, in this embodiment, the linear valve 17 is arranged between the pipeline A1 and the M/C 3. Accordingly, the brake pressure is regulated based on the differential pressure between the M/C pressure and the W/C pressure.

10 With this construction, the control valve 443 is closed at the W/C low pressure timing. Therefore, the brake fluid is supplied to the first chamber 9b based on the discharge pressure by the pump 8, thereby driving the step piston 9a. Then, if the step piston 9a moves by a predetermined distance, the spool valve unit 440 is opened and the brake fluid is provided to the third chamber 9g. As a result, the step piston 9a is moved based on the differential pressure between the first and third chamber 9b, 9g and the second chamber 9c.

15 Further, if the step piston 9a further moves by a predetermined distance, the spool valve unit 441 is opened, and
20 the brake fluid is also provided to the fourth chamber 9n.

25 When the A2 is selected as the pressurizing path, the control valve 443 is opened. Therefore, the pipeline R1 plays a role of pressurizing path in place of the pipeline A2. The discharge pressure of the pump 8 is supplied to the W/C 4, 5 via the pipeline R1, and not via the pipeline A2. Accordingly, the brake fluid reserved in the third and fourth chamber 9g, 9n is returned to the discharge port side of the pump 8 via the pipeline R2 through

the check valves 446, 447.

As a result, the step piston is returned to the initial position and will move speedy if the amplifying function is demanded later.

5 (Twenty-seventh embodiment)

An urgency control such as ABS control can be executed by each brake system shown in each of the above embodiments. For example, ABS control is executed as follows.

FIG. 36-38 show flow diagrams to be executed by the brake system. The brake system in the first embodiment is used as one example of this embodiment. This processing is basically the same processing as the FIG. 2-5, and therefore only different point is described.

10
15
20 First, at steps 101-107, each processing as in the FIG. 2 is executed step by step. Then, at step 501, whether the ABS control is executed or not is determined. This is determined by a flag or the like that is set when the ABS control starting condition is satisfied. The processing advances to step 502 in response to an affirmative determination (Yes), and the ABS control is executed. The detail of the ABS control is described later.

On the other hand, the processing advances to step 108 in response to a negative determination (No), and the amplifying piston bypass change processing is executed. This processing is the same as shown in FIG. 3 in the first embodiment. Then, the
25 processing advances to the step 503 to determine whether or not the ABS control starting condition is satisfied. The ABS control starting condition is the same as the well known conditions, i.e.,

when the slip ratio calculated based on the sensing signals from the wheel speed sensors 22, 23 exceeds a predetermined threshold level.

5 The flag indicative of a state under the ABS control is set in response to an affirmative determination (Yes), and then the ABS control processing is executed at step 502. To the contrary, the brake control ECU 1 executes the processing after step 109, which is shown in FIG. 37, in response to a negative determination (No). Moreover, if the flag is still setting, the brake control ECU 1 make the flag reset. Those processing after step 109 are similar to the processing shown in FIG. 2 in the first embodiment.

FIG. 38 shows the ABS control processing at step 502.

10 First, when the ABS control processing starts, motor full rotation is executed at step 530. Then, the motor 7 is rotated so that the brake fluid to be depressurized at the ABS depressurization timing can be sucked by the pump 8 to depressurize the W/C pressure. The processing advances to the step 521, and a calculation for the ABS control is executed. This calculation is executed at an usual ABS control timing, i.e., the wheel speed, 15 an estimate vehicle speed, the slip efficiency and the like are calculated.

20 The processing advances to step 522 to determine whether the ABS control end condition is satisfied or not. For example, the ABS control end condition is "when the vehicle is stopped". 25 The processing advances to the step 523 in response to an affirmative determination (Yes). The ABS control end processing, for example, each solenoid of the control valve is turned off. Then the

processing returns to step 106. To the contrary, the processing advances to the step 524 in response to a negative determination (No), and the control signal is output to each wheel. That is, a preferable control way (pressurizing, maintaining or depressurizing) to be executed is determined. Then, a signal for executing the determined control is output. As a result, each of the control valves is controlled according to the determined control.

Next, the processing advances to steps 525, 526 to determine whether the amplifying piston 9 should be used or not. Specifically, the step 525 determines whether or not the signal outputted at step 524 is a signal that controls one wheel whose W/C pressure is depressurized and the other wheel whose W/C pressure is maintained in each brake piping. Moreover, the step 526 determines whether or not the signal outputted at step 524 is a signal that controls both wheels whose W/C pressures are depressurized in each brake piping. Namely, when the pressurization of the W/C pressure is required, the amplifying piston 9 should be used, and therefore the brake control ECU 1 selects which case is applicable. For example, these control signals mean the output signal for controlling at least one of the wheel whose W/C pressure is pressurized, or the output signal for controlling both of the wheels whose W/C pressures are maintained with a possibility of changing later into an output signal for pressurizing both of the wheels.

The processing advances to step 527 in response to an affirmative determination at step 525 or 526 to execute the

amplifying piston return processing. For example, the first control valve 10 is set to the open position, and the second control valve 11 is set to closed position so that the amplifying piston 9 is returned. After this processing, the processing advances to step 112. Then the processing as shown in FIG. 2 in the first embodiment is executed.

On the other hand, the processing advances to the step 528 in response to a negative determination at steps 525, 526 to execute a switching trigger sensor signal input calculation. And, then, the processing advances to step 529 to determine whether the amplifying piston 9 is switched or not. The processing advance to step 530 in response to a negative determination (No) to determine the piston bypass changing condition is satisfied or not. To the contrary, the processing advance to step 532 to determine the amplifying piston bypass changing end condition is satisfied or not.

Next, the processing advances to step 531 in response to an affirmative determination (Yes). Then, the amplifying piston bypass changing processing is executed, and the processing advances to step 112. The processing advances to step 533 in response to a negative determination (No) to execute the amplifying piston bypass end processing. Then, the processing advances to step 112. To the contrary, the processing advances to 112 in response to a negative determination (No) at step 530 or 532. Those processing after step 428 are similar to the processing at steps 301-304, 307 and 308 shown in FIG. 4 in the first embodiment.

The ABS control timing, the amplifying piston 9 is returned

to the initial position side, according to the requirement of use of the amplifying piston 9. As a result, the amplifying piston 9 can move speedy if the amplifying function is demanded later. The brake system in which the pressurizing path is changed over can execute the ABS control in this manner.

FIG. 39 is a referential time diagram when the processings shown in FIGs. 36-38 are executed. This shows the case that the ABS control is executed. The vehicle speed calculated based on the sensing signals from the wheel speed sensors 22, 23, the pedal pressure of the brake pedal 2, the brake fluid pressure (the discharge pressure of the pump 8, the M/C pressure, the W/C pressure), stroke amount of the amplifying piston 9, the ON/OFF condition of the first and second control valves 10, 11, the duty ratio of the current to the linear valve 17 and the duty ratio of the current to the motor 7 are shown in FIG. 39.

The changes of the elements shown in the time diagram are basically the same as in FIG. 6. However, the change at the ABS control during the period between t_1 and t_3 are different from those of FIG. 6.

First, the ABS control starts at term t_1 . Then, the condition of each wheel that should be controlled, i.e., pressurizing condition, maintaining condition or depressurizing condition, is determined based on the calculated result of the ABS control calculation. For example, the front right wheel Fr side is controlled as the depressurizing condition, and the rear right wheel Rr side is controlled as the maintaining condition as in the FIG. 39. At the same time, the second control valve 11 is

opened, and, therefore, the first and second chambers 9b, 9c become the same pressure. As a result, the amplifying piston 9 is returned to the initial position side (See step 527).

Next, when the both of wheels are controlled as the maintaining condition at term t2, the amplifying piston 9 stops returning. Further, when one of wheels is controlled as the pressurizing condition (pulse pressurization), the W/C 4, 5 are pressurized again by using the amplifying piston 9. Then, such processing continues during the terms t1-t3.

As mentioned above, the W/C 4, 5 can be pressurized by using the amplifying piston 9 while the ABS control is executed. Therefore, each of the wheels can be pressurized with high response.

(Modifications)

In the above embodiments, the brake systems has the rotating pump or the like as the pump 8, but may have the other type of pump such as a piston pump.

In steps 303, 305, 306 of the first embodiment, the trigger conditions for changing pressurizing path from the pipeline A1 to the pipeline A2 are only examples. Accordingly, a part of these conditions or the other conditions may be employed.

In steps 305, 306 of the first embodiment, the pipeline A2 is selected as the normal braking that does not require high pressurization, or not at the urgency braking. However, the selection of the pipeline A2 is not essential.

In the first embodiment or the like, the pipeline A2 is connected between the discharge port side of the pump 8 and the first chamber 9b. However, the pipeline A2 may be connected to

any position where fluid pressure is the same as the first chamber 9b. That is, the pipeline A2 has only to be connected to the first chamber 9b.

In the twenty-seventh embodiment, the pipeline A1 is
5 selected to use the amplifying piston 9 at the urgency control time. However, there is a possibility that the urgency control needs longer time. Therefore, in order to pressurize the W/C 4, 5 directly, the pipeline A2 may be selected always when the urgency control is required.